



## IDROMAR SUPERMINI 30 NAUTICAL WATERMAKER WITH CAPACITY 30 LT/H

Reference: SUPERMINI 30

### IDROMAR SUPERMINI 30 NAUTICAL WATERMAKER WITH CAPACITY 30 LT/H

The Idromar SUPERMINI 30 nautical watermaker has an hourly production of fresh water at 25 ° C equal to 30 liters/hour and a daily production at 25 ° C equal to 720 liters/day.

Idromar SUPERMINI 30 is an incredibly reliable small boat watermaker. Designed specifically for marine applications and is made of materials that are completely impervious to brackish water.

Idromar SUPERMINI 30 is a small size watermaker for boats, incredibly reliable. Designed specifically for marine applications and made with materials that are completely unassailable by brackish water.

One of the main features of the Idromar SUPERMINI 30 watermaker is the use of 316L stainless steel: from the small details such as screws, bolts and nuts, the entire frame, the vessels containing the membranes and the head of the high pressure pump built in stainless steel to eliminate the phenomenon of corrosion.

The Idromar SUPERMINI 30 watermaker provides a practical and reliable source of fresh water to boaters with high supply requirements.

The use of the Idromar SUPERMINI 30 nautical watermaker is extremely simple, as no adjustment is necessary. In fact, all systems are equipped with automatic pressure regulation. No direct access to the watermaker is therefore necessary.

#### TECHNICAL CHARACTERISTICS OF IDROMAR SUPERMINI 30:

Production at 25: 30 lt / h  
Production at 25: 720 lt / d  
Water salinity: 300/400 ppm  
Consumption: 1.1 Kw  
Sea suction : 3/4 "  
Box suction: 3/4"  
Overboard discharge: 3/4 "  
Water produced: 1/2"  
Width: 460 mm  
Depth: 250 mm  
Height: 450 mm  
Net weight: 50 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to IDROMAR watermakers or other specialized brands.

The images and technical data are not binding and may be subject to revisions by the manufacturer.

## Technical Sheet

Power (W)	1100
Length (mm)	460
Width (mm)	250
Height (mm)	450
Feed Type	230 V
Production for hour at 25°C (Lt/h)	30
Daily production at 25°C (Lt/day)	720
Salinity of water produced (PPM)	300/400
Capacity (Lt/h)	30
Remote panel	Digital
Weight (Kg)	0.4