



TECNOGEN TENAK MI17TK

Reference: MI17TCSS

The TENAX series comprises diesel generator sets, 1500 rpm water- or air-cooled, with power ratings from 5.5 to 2255 kVA max, delivering three-phase 400/230 V voltage.

Available in both open base and super-silenced versions, they are equipped with silenced version, they are equipped with Perkins, John Deere industrial engines, Iveco Aifo or Lombardini engines and alternators from world leading brands such as Leroy Somer, Stamford, Mecc Alte or Marelli.

The enclosures, designed to guarantee an excellent level of level of soundproofing and optimum engine cooling, are entirely made of hot-dip galvanised steel and subsequently painted with polyester powder, making them practically unassailable by atmospheric agents.

against atmospheric agents. Due to their characteristics, these machines suitable for continuous use in the industrial sector.

industrial environment and, in the super-silenced versions, for applications with switchgear in the civil sector. They are also available on request with different engines, including Cummins, Volvo, Deutz and including Cummins, Volvo, Deutz and Mitsubishi.

The image is purely indicative.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	13.2
Maximum power three phase (KVA)	16.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	mitsubishi S4L261SD
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	1649
Number cylinders	4
Cooling	Water
Consumption (L/h)	3.3
Length (mm)	1500
Width (mm)	750
Height (mm)	1300
Dry weight (Kg)	400
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	Digital AVR
Engine manufacturer	Mitsubishi