



GENERATOR THREE-PHASE 20,7KVA AVR STAGE V

Reference: GT207KVA AVRSV

GENERATOR THREE-PHASE 20,7KVA AVR STAGE V

The generator single-phase / three-phase is equipped with an OHV1000 Stage V petrol engine, capable of delivering a power of 20.7KVA, complete with **AVR voltage regulator**.

The Generator adapts perfectly to the most varied uses, thanks to the handling trolley that allows it to be relocated in perfect safety and simplicity. Thanks to the increased tank of 65 l, this generator has an extraordinary autonomy of 6.6 h with 75% of the load.

These generators are equipped with high quality components, light weight, compact, ease of use and also the modern design, equipped with a practical electric start.

The generator alternator is synchronous, single-phase, self-excited, self-regulated, brushless with class H insulation and with AVR regulator.

The advantages of the AVR voltage regulator

The automatic voltage regulator, or AVR, allows the generator to deliver stable energy and therefore be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator is therefore ideal for home use, camping, for hobby and free time, but also for construction sites and craftsmen.

TECHNICAL FEATURES

Type of phase: Single-phase / Three-phase

Maximum single-phase power: 20.7 KVA / 16.5 KW

Maximum three-phase power: 20.7 KVA / 16.5KW

Voltage: 230 / 400 V

Frequency: 50 Hz

Engine: OHV1000

Fuel: Petrol

Engine rpm: 3000 rpm

Emissions standard: Stage V

Number of cylinders : 2

Displacement: 999 cc

Tank capacity: 65 l

Consumption: 9.8 l @ 75%

Autonomy: 6.6 h

Alternator: Brushless self-excited

Voltage regulator: AVR

Socket configuration: 1 x schuko - 1 x 63A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC

Width: 970 mm
 Length: 680 mm
 Height: 955 mm
 Dry weight: 255 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the full range of specialized brand generators

Non-binding images and technical data.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	16.5
Maximum power single phase (KVA)	20,7
Maximum power three phase (KW)	16,5
Maximum power three phase (KVA)	20,7
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x schuko - 1 x 63A 3P 230V - 1 x 32A 5P 400V - 1 x 12 VDC
Engine	OHV1000
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	999
Number cylinders	2
Alternator	Self-excited Brushless
Fuel tank capacity (L)	65
Consumption (L/h)	9.8 l @ 75%
Running time (h)	6.6 at 75% of the load
Length (mm)	970
Width (mm)	680
Height (mm)	955
Dry weight (Kg)	255
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS

Voltage regulator

AVR