



CUMMINS C55D5EQ GENERATOR 55KVA SINGLE-PHASE/THREE-PHASE OPEN

Reference: C55D5EQ-A

CUMMINS C55D5EQ GENERATOR 55KVA SINGLE-PHASE/THREE-PHASE OPEN

The CUMMINS C55D5EQ generator is equipped with a Cummins 4BTAA3,3-G14 engine powered by diesel and is capable of delivering a maximum power of 55KVA, complete with compound voltage regulator.

The CUMMINS C55D5EQ is equipped with **PowerStart 600** control unit which allows you to view all the electrical parameters of the engine and generator, the functions, the status of the generator set, manage the entire group and view, in case they occur, system errors or alarms. Controller provides simple interface, auto/manual and remote start/stop control and stop fault indication. The integration of all control functions in a single command ensures greater reliability and performance compared to conventional generator set control systems.

The Generator is equipped with electric start and with low fuel consumption, in fact it consumes about 9 litres/hour at 75% of the load for an autonomy of up to 21 hours of operation. The generator set guarantees efficient and silent operation thanks to the Cummins 4BTAA3.3-G14 engine, which allows it to deliver a maximum power of 55KVA.

In addition, it is equipped with automatic starting via the ATS panel, which allows it to be switched on autonomously in case of blackout.

Thanks to the advanced control unit, the generator is equipped with:

- PC based software service tool
- Inpower Modbus interface for interconnection with PLC/BMS
- Configurable inputs and outputs
- Configurable alarm inputs to cause a shutdown or warning response

ATS AUTOMATIC STARTER PANEL ARRANGEMENT

The CUMMINS C55D5EQ generator is designed for connection to ATS automatic starter panel. Thanks to which you will no longer have to worry about blackouts, since, in the event of a power failure from the mains, this panel is able to turn on the group and will allow you to continue your business without losing your work data.

CUMMINS C55D5EQ TECHNICAL SPECIFICATIONS

- Phase type: Single-phase / Three-phase
- Continuous power: 50 KVA / 40 KW
- Maximum power: 55 KVA / 44 KW
- Engine: Cummins 4BTAA3,3-G14
- Fuel system: Diesel
- Engine speed: 1500 rpm
- Regulation of revolutions: Mechanical

Alternator: Stamford UC224D
Emissions standard: Stage III A
Starter: Electric / Automatic
Voltage regulator: Compound
Voltage: 230/400 V
Frequency: 50 Hz
Socket panel: Terminal box
Tank capacity: 200 l
Consumption at 75% load capacity: 9.52 l/h
Autonomy at 75% load: 21 h
Length: 2315 mm
Width: 1015 mm
Height: 1480 mm
Weight a dry: 969 kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the full range of CUMMINS generators and other specialized brands.

Non-binding images and technical data

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	44
Continuous power three phase (KW)	
Maximum power three phase (KVA)	55
Continuous power three phase (KVA)	
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	
Emissions Regulations	STAGE 3A
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	
Number cylinders	4
Cylinders' position	In line
Alternator	Synchronous, brushless
Poles	4
Fuel tank capacity (L)	
Consumption (L/h)	

Running time (h)	21 at 75% of the load
Length (mm)	
Width (mm)	
Height (mm)	1480
Dry weight (Kg)	969
Silenced	No
Super silenced	No
Brushes	No
Product type	Generator
Control unit	
ATS Switch device	Optional ATS
Type of alternator	Constant Speed
Voltage regulator	Compound
Engine manufacturer	Cummins
Precision of voltage regulation	