



ECOFLOW DELTA2 PORTABLE BATTERY 1,8 KW SOLAR RECHARGE

Reference: 5003601004

ECOFLOW DELTA2 PORTABLE BATTERY 1,8 KW SOLAR RECHARGE

The ECOFLOW DELTA2 portable battery is a practical solution for having access, in any situation, to a silently silent energy source with zero CO₂ emissions.

ECOFLOW DELTA2 is a portable battery with a huge capacity of approximately 1 kWh, this guarantees hours of reserve energy. The ECOFLOW DELTA2 portable battery inverter's large load is capable of supporting even DIY tools up to 1800W (2700W peak, pure sine wave).

This battery can be recharged in multiple ways, to adapt to any situation. Plug-in charging, car charging and more, it's also a portable solar power station. With EcoFlow panels, full recharge takes place in just 4 hours. Power up to 11 devices simultaneously via AC, DC or USB outlets. Ideal as an emergency group in the event of a blackout.

Thanks to its innovative technology, it ensures you up to 10 years of daily use up to 80% of its original capacity. This is thanks to the LiFePO₄ battery chemistry that guarantees over 3,000 full charge and discharge cycles and 6 times the industry average.

TECHNICAL CHARACTERISTICS ECOFLOW DELTA2:

INPUTS

AC charge voltage: 220-240 VAC
AC charge power: 1100 W
Solar input: 500 W, 11-60 Vdc 15A
Car charger input: 12 V/24 Vdc 8A

OUTS

n°4 AC Schuko outputs: 1.8 KW continuous, 2.7 KW peak, 220 Vac, 50 Hz
n°2 DC5521: 38 W 12.6 Vdc, 3A A
n°2 USB-A: 12 W per port, 5 Vdc, 2.4 A
n°2 USB-A for fast charging: 18 W 5 Vdc, 2.4 A/ 9Vdc, 2 A/ 12 Vdc, 1, 5 A
n°2 USB-C: 100 W 5/9/12/15/20 Vdc, 3 A
n°1 car output: 126 W 12.6Vdc, 10 A

GENERAL INFORMATION

Solar charge connector: MC4
Capacity: 1024 Wh
Cell type: Lithium Ion
Life cycle: 3000 cycles

Width: 400 mm
Length : 211 mm
Height: 281 mm
Weight: 12 kg

Are you looking for a portable battery with different technical characteristics? [HERE](#) you can find the area dedicated to portable batteries and UPS of specialized brands.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	2.7
Continuous power single phase (KW)	1.8
Length (mm)	400
Weight (Kg)	12
Life span	3000