



WFM SPD7500E GENERATOR 6,4KVA DIESEL SINGLE-PHASE AVR

Reference: SPD7500E AVR

WFM SPD7500E GENERATOR 6,4KVA DIESEL SINGLE-PHASE AVR

The WFM SPD7500E single-phase generator is equipped with a KOHLER 15LD440 diesel-powered engine, and is complete with **AVR** voltage regulator.

The generator is equipped with electric start and has low fuel consumption, in fact it consumes only 1.2 litres/hour at 75% of the load for an autonomy of up to 16.6 hours of operation.

The WFM SPD7500 provides reliable power for home, business and entertainment environments Safely power household appliances and other electronic devices Power solution for outdoor parties. Extremely practical sockets and controls facilitate starting and running the generator, making these operations extremely simple and fast.

The generator has a practical double-curved handle, to facilitate mobility and storage. It has a completely steel structure and a tank with a maximum capacity of 20 liters. The generator guarantees efficient and silent operation thanks to the KOHLER 15LD440 engine which allows to deliver a maximum power of 6.4KVA.

TECHNICAL SPECIFICATIONS WFM SPD7500:

Phase type: Single-phase
Continuous use power: 6.4 KVA / 5.8 KW
Maximum power: 7.5 KVA / 6.8 KW
Motor: KOHLER 15LD440
Engine speed: 3000 rpm
Emissions standard: Not Emissions
Starter: Electric
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 1 x Schuko 16A 230V / 1 x 16A 230V CEE / 1 x 32A 230V CEE
Tank capacity: 20 l
Autonomy at 75% load: 16.6 h
Consumption at 75% load: 1.2 Lt /h
Sound pressure: 95 dB
Length: 750 mm
Width: 560 mm
Height: 620 mm
Dry weight: 160 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to WFM generators or other specialized brands.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	6.8
Continuous power single phase (KW)	5.8
Maximum power single phase (KVA)	7.5
Continuous power single phase (KVA)	6.4
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 400V 16A 5P CEE - 1 x 230V 16A 3P CEE
Engine	Kohler 15LD440
Emissions Regulations	Not Emitted
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	442
Cooling	Air
Fuel tank capacity (L)	20
Consumption (L/h)	1.2 al 75% del carico
Running time (h)	
Acoustic power	95 dB(A)
Acoustic pressure	71 dB(A) at 7 m
Length (mm)	750
Width (mm)	560
Height (mm)	620
Dry weight (Kg)	160
Silenced	Yes
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Kohler