



## GENERAC LT VTEVOQ LIGHT TOWER 4x320W G4 LED WITH GENERATOR 5KW STAGEV

Reference: LS06K20-0000EU

### GENERAC LT VTEVOQ LIGHT TOWER 4x320W G4 LED WITH GENERATOR 5KW STAGEV

GENERAC LT VTEVOQ is a light tower equipped with four 320W Led floodlights that can be lifted up to a height of 7,5 m, capable of illuminating an area of 4500 m<sup>2</sup>.

The GENERAC LT VTEVOQ is equipped with a Kubota Z482 StageV Diesel engine, which in combination with the capacious 120 l tank manages to guarantee a working autonomy of 171 h. The GENERAC LT VTEVOQ has an extremely quiet operation, in fact it has a sound emission of only 63 dB(A) at 7m.

The Generac LT VTEVOQ, thanks to 4 LED floodlights can illuminate an area of 4500 square meters with a maximum luminous intensity of 188160 lm total. The light tower is equipped with a galvanized mast with a winch manual system that allows the floodlights to be raised to a maximum height of 7.5m. The winch is equipped with an anti-fall safety system that blocks its access and accidental release once positioned.

Ideal for lighting construction sites, parking lots, emergency sites, outdoor events, and other applications where intense, long-lasting illumination is needed in low light conditions.

#### TECHNICAL FEATURES GENERAC LT VTEVOQ

Lamp power: 4 x 320 W  
Lamp type: LED  
Total lumens: 188160 Lm  
Illuminated area: 4500 m<sup>2</sup>  
Lifting system: Manual  
Pole rotation: 340°  
Engine: Kubota Z482  
Emission standard: StageV  
Engine Cooling: Liquid  
Cylinders (N): 2  
Engine speed (50/60 Hz): 1500 / 1800 rpm  
Alternator (kVA/V/Hz): 3.5/220/50 - 4.2/240/60  
Electrical outlet (kVA/V/Hz): 2/220/50 - 2/240/60  
Average sound pressure: 63 dB(A) @ 7m  
Wind resistance: 80 km/h  
Tank capacity: 120 l  
Autonomy: 171 h  
Minimum dimensions (W x D x H): 2480 x 1190 x 1950 mm  
Maximum dimensions (W x D x H): 2480 x 2400 x 7500 mm  
Dry weight: 620 kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the towers or other specialized brands.

Non-binding images and technical data.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.5
Maximum power single phase (KVA)	3.5
Fuel	Diesel
Voltage (V)	230
Engine	Kubota Z482
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500 / 1800
Number cylinders	2
Cooling	Coolant Liquid
Type of lamps	LED
Lamps	4 x 320 W
Illuminated area (m <sup>2</sup> )	4500
Total lumens (Lm)	188160
Lifting System	Manual lifting system
Maximum height (m)	7.5
Mast rotation	340°
Open size (mm)	2480 x 2400 x 7500
Closed size (mm)	2480 x 1190 x 1950
With generator / Without generator	With generator
Transportability	Stationary
Stability to wind (Km/h)	80 Km/h
Fuel tank capacity (L)	120
Running time (h)	171
Acoustic pressure	63 dB(A) at 7 m
Dry weight (Kg)	620
Engine manufacturer	Kubota