



PRAMAC LIFTER GS EVO 30 S2 TRANSPALLET MANUAL 1150x525 SINGLE ROLLER

Reference: TEF41AVY100

PRAMAC LIFTER GS EVO 30 S2 TRANSPALLET MANUAL 1150x525 SINGLE ROLLER

The Pramac Lifter GS Evo 30 S2 is; a hand pallet truck designed to transport loads weighing up to 3000 kg. This pallet truck is equipped with a standard fork 1150 mm long and 525 mm wide, able to easily adapt to most transport needs.

The ergonomic design of the pallet truck, with a lever handle and a hydraulic pump lifting system, allows for easy maneuverability and quick and safe lifting of loads. Furthermore, the integrated braking system ensures precise control of the pallet truck in any loading and unloading situation.

The Pramac Lifter GS Evo 30 S2 is; equipped with a high-strength steel frame, which guarantees greater durability and greater stability; during the transportation of loads. Furthermore, the pallet truck is; equipped with an accident prevention system, with a quick release mechanism of the forks in the event of a collision or impact.

This hand pallet truck is designed to be used in a variety of ways. easy to maintain and requires minimal maintenance due to its robust construction and quality; of the materials used. Additionally, the pallet truck's compact and lightweight design allows for easy transportation and storage, making it an ideal option for small to medium-sized warehouses and warehouses.

TECHNICAL FEATURES PRAMAC LIFTER GS EVO 30 S2

Type of propulsion: Manual
Lifting: Manual
Guide system: Accompanying
Load capacity: 3000 kg
Front tyres: NYLON/POLY
Rear tyres: POLY
Front track: 155 mm
Rear track: 375 mm
Lift height: 115 mm
Drawbar height in driving position max: 1185 mm
Drawbar height in driving position min: 710 mm
Height of forks lowered: 85 mm
Total length: 1550 mm
Unit length: drive: 400 mm
Total width: 525 mm
Fork dimensions - Thickness: 50 mm
Fork dimensions - Width: 150 mm
Fork length: 1150 mm
Fork width : 525 mm
Free light in the middle; wheelbase: 35 mm
Stow aisle for 800x1200 pallets: 2085 mm

Turning radius: 1367 mm
 Service weight: 88 Kg

Are you looking for a pallet truck with different technical characteristics? [HERE](#) you can find the area dedicated to pallet trucks PRAMAC or other specialized brands

Non-binding images and technical data.

Technical Sheet

Drive	Manual
Operator type	Pedestrian
Load capacity (Kg)	3000
Load centre distance (mm)	600
Load axle to end forks (mm)	932
Wheel base (mm)	1192
Service weight (Kg)	88
Axle load, laden rear (Kg)	2196
Axle load, laden front (Kg)	892
Axle load, unladen front (Kg)	59
Axle load, unladen rear (Kg)	29
Tyres: front wheels	POLY.I. / NYLON
Tyres: rear wheels	NYLON
Diameter steering wheels (mm)	200
Width steering wheels (mm)	55
Diameter load rollers (mm)	82
Width load rollers (mm)	60
Quantity rear wheels	4
Rear balancing axle	No
Tread front (mm)	155
Tread rear (mm)	375
Lift height (mm)	115
Height of tiller in drive position max (mm)	1185
Height lowered (mm)	85
Overall length (mm)	1550
Length to face of forks (mm)	400
Overall width (mm)	525

Thickness fork (mm)	50
Width fork (mm)	150
Lenght fork (mm)	1150
Distance between fork arms (mm)	525
Ground clearance at centre of wheelbase (mm)	35
Aisle width (mm)	2048
Turning radius (mm)	1367
Lifting speed laden (strokes)	13
Lifting speed unladen (strokes)	13
Weigher	No