



OSMOSEA CLASSIC 240S NAUTICAL/LAND FACILITIES WATERMAKER 200 LT/H

Reference: A-0000002327

OSMOSEA CLASSIC 240S NAUTICAL/LAND FACILITIES WATERMAKER 200 LT/H

The watermaker OSMOSEA CLASSIC 240S is a monoblok reverse osmosis plant equipped with 2 carbon 2540 vessel, capable of supplying up to 200 lt/h of fresh water.

The OSMOSEA CLASSIC 240S watermaker is designed to remove salt and other impurities from sea or brackish water, making it drinkable and usable for daily needs on board or ashore. Operation of the watermaker is quite simple and is based on a reverse osmosis process.

The OSMOSEA CLASSIC 240S is equipped with a high-pressure pump, which pushes seawater through the membrane, once purified it is then stored in a special tank, ready for use.

The watermaker is capable of producing up to 200 liters of purified water per hour, depending on salinity conditions and ambient temperature. The system is also equipped with automatic sensors and controls to ensure safe and efficient operation.

The OSMOSEA CLASSIC 240S watermaker is capable of removing 99.4 percent of salts and impurities in sea or river water. Thanks to its compact and lightweight one-piece design, it can be easily installed on any boat or in any land environment without taking up too much space.

An excellent choice for those looking for a reliable and high-quality desalination system, thanks to its production capacity this watermaker can meet the needs of a wide range of users, both at sea and on land. In addition, the system is designed to be easy to operate and maintain, with a number of built-in safety features to ensure maximum protection for the user and the system itself.

TECHNICAL FEATURES OSMOSEA CLASSIC 240S

Production: 200 lt/h
Daily Production: 4800 lt/day
Vessel Number: 2
Vessel Type: 2540 Carbon
Membranes: Tri-polyamide high efficiency
Prefilters: 30 micron + 5 micron
Postfilter: activated carbon
Salt expelled: 99.4%
Pressure adjustment: Manual
Salinity monitoring: Automatic
Maximum use salinity: 50000 ppm
Power supply voltage: 110 / 230 / 400 V
Frequency: 50 / 60 Hz
Installed power: 2.17 KW

Frame: stainless steel
Length: 1200 mm
Width: 350 mm
Height: 408 mm
Net weight: 75 kg

Are you looking for a water maker with different features? [HERE](#) you can find the area dedicated to OSMOSEA watermakers or other specialized brands.

Non-binding images and technical data.

Technical Sheet

Frequency (Hz)	50
Power (W)	2170
Length (mm)	1250
Width (mm)	435
Height (mm)	440
Feed Type	110 / 230 / 400 V
Production for hour at 25°C (Lt/h)	200
Daily production at 25°C (Lt/day)	4800
Remote panel	Analogic
Weight (Kg)	75