

OSMOSEA EVO 240L NAUTICAL/LAND FACILITIES WATERMAKER 480 LT/H

Reference: A-0000002310



OSMOSEA EVO 240L NAUTICAL/LAND FACILITIES WATERMAKER 480 LT/H

The OSMOSEA EVO 240L watermaker is a one-piece reverse osmosis plant equipped with 2 carbon 4040 vessels, capable of supplying up to 480 lt/h of fresh water.

The OSMOSEA EVO 240L is designed to remove salt and other impurities from seawater or brackish water, ideal for use aboard boats and yachts, but can also be used in other situations such as campgrounds, mountain lodges, and isolated homes.

The watermaker can produce up to 480 liters of purified water per hour, depending on salinity conditions and ambient temperature. The system is also equipped with automatic sensors and controls to ensure safe and efficient operation.

The OSMOSEA EVO 240L watermaker can remove 99.4 percent, making it safe for consumption. Thanks to salt removal, the water tastes neutral and can be used for drinking, cooking and washing.

Its operating system makes the OSMOSEA EVO 240L watermaker extremely quiet and easy to operate, thanks to the presence of a touch screen display that allows you to monitor and control the fresh water production process. The display also provides useful information on the salinity level of the produced water and system performance. The OSMOSEA EVO 240L watermaker is built with high-quality materials, such as titanium, which provides greater resistance to corrosion and external agents.

TECHNICAL FEATURES OSMOSEA EVO 240L

Production: 480 lt/h
Daily Production: 11520 lt/day
Vessel Number: 2
Vessel Type: 4040 in Carbon
Membranes: high efficiency
Prefilters: 2 X activated carbon
Postfilter: Activated carbon
Salt Expelled: 99.4%
Pressure adjustment: Automatic
Salinity monitoring: Automatic
Maximum use salinity: 50000 ppm
Power supply voltage: 110 / 230 / 400 V
Frequency: 50 Hz
Installed power: 4.8 KW
Frame: stainless steel
Length: 1300 mm
Width: 498 mm
Height: 768 mm
Net weight: 150 kg

Are you looking for a water maker with different features? [HERE](#) you can find the area dedicated to OSMOSEA watermakers or other specialized brands.

Non-binding images and technical data.

Technical Sheet

Frequency (Hz)	50
Power (W)	3500
Length (mm)	1300
Width (mm)	498
Height (mm)	768
Dry weight (Kg)	150
Feed Type	110 / 230 / 400 V
Production for hour at 25°C (Lt/h)	480
Daily production at 25°C (Lt/day)	11520
Remote panel	Digital touch screen