



## WEBASTO BLUECOOL C-40T NAUTICAL CHILLER AIR CONDITIONER 40000 BTU/h

Reference: WBCL1207002D

### WEBASTO BLUECOOL C-40T NAUTICAL CHILLER AIR CONDITIONER 40000 BTU/h

Webasto BlueCool C-40T is a chilled water nautical air conditioner (chiller) suitable for use on boats, with a rated cooling capacity of 40000 BTU/h.

The Webasto BlueCool C-40T is a nautical air conditioner designed to provide an effective and reliable solution for air conditioning the indoor environment of boats. Thanks to its cooling capacity, the air conditioner ensures optimal comfort in all weather conditions.

The Webasto BlueCool C-40T is a water chiller that uses a refrigeration circuit to cool water and then distributes it through a system of pipes and fans. This method of cooling offers many advantages, including quiet operation and even distribution of cool air inside the boat.

The system is designed for easy and convenient installation aboard boats. Its compact size and sleek design allow it to blend harmoniously into its surroundings. In addition, the system features an intuitive display for easy and precise control of temperature settings and other functions.

The Webasto BlueCool C-40T chiller air conditioner can provide cooling to different areas of the boat, allowing the temperature in each room to be adjusted separately. This provides precise control of thermal comfort and the ability to meet the individual preferences of each passenger on board.

The advanced technology of the Webasto BlueCool C-40T ensures quiet operation, allowing you to enjoy a cool and comfortable environment without annoying noise. In addition, the system is designed to be highly energy efficient, helping to reduce fuel consumption and operating costs.

The WEBASTO BLUECOOL C-40T comes complete with:

- electronics
- blower
- Touch Screen remote panel with 4.5 m cable

### TECHNICAL FEATURES WEBASTO BLUECOOL C-40T

Cooling capacity: 40000 BTU/h / 11700W  
Heating Capacity: 40000 BTU/h / 11700W  
Power Supply Voltage: 230V  
Frequency: 50 / 60 Hz  
Operating current consumption: 14 / 16 A  
Minimum cold water flow rate: 32 l/min  
ø cold water connection: 1"

Ø seawater connection: 1"  
Minimum seawater flow rate: 34 l/min  
Max. permissible ambient temperature: 45 °C  
Refrigerant: R410a  
Refrigerant quantity: 2x650 g  
Width: 590 mm  
Depth: 410 mm  
Height: 500 mm  
Net weight: 70 kg

Looking for a product with different technical characteristics? [Here](#) you can find the area dedicated to nautical air conditioners WEBASTO or other specialized brands.

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Refrigerating yield	40000 BTU/h / 11700 W
Heating power	40000 BTU/h / 11700W
Absorbed average current, refrigerating (A)	14 / 16
Length (mm)	590
Width (mm)	410
Height (mm)	500
Product type	Air conditioner
Coolant	R410A
Weight (Kg)	70