



GENERATOR 10 KVA SUPER SILENCED SINGLE PHASE STAGEV

Reference: GD10KVAM

GENERATOR 10 KVA SUPERSILENCED SINGLE PHASE STAGEV

The Generator single phase is equipped with Kubota D1105 STAGEV engine with Diesel power supply, able to deliver a power of 10 KVA.

This generator is equipped with electric start, with 12 V battery and enclosure that lowers noise emissions and makes it supersilenced.

The group is equipped with a soundproof cabin, thanks to which there is a drastic reduction of noise pollution up to 70 dB recorded at a distance of 7 meters, thanks to these features the group can be considered super silenced.

The generator guarantees efficient and silent operation thanks to the Kubota D1105 engine, which can deliver a maximum power of 10KVA.

The generator includes:

- Automatic engine stop device with warning lights for:
 - battery charge failure
 - high water temperature
 - low fuel level
 - low oil pressure
- 1 single-phase EEC 230V - 32A socket
- 1 single-phase 230V socket
- 12 V battery
- Power output protections
- Differential switch
- Voltmeter
- Hour meter
- Emergency stop button
- Fork passage

STAGEV EMISSION STANDARDS

This Generator is equipped with STAGEV "mobile" motorization, as required by the European Regulation 2016/1628. These new motorizations allow to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in environmental impact of 200% compared to standard motorizations.

TECHNICAL FEATURES

Phase Type: Single-Phase

Maximum Single-Phase Power: 10 KVA / 8 KW
 Continuous Single-Phase Power: 9 KVA / 7.2 KW
 VAC Voltage: 230 V
 Frequency (Hz): 50
 Starting Frame: Electric
 Engine: Kubota D1105
 Emissions Standard: STAGE V
 RPM: 1500
 Power supply: Diesel
 Fuel tank capacity: 40 l
 Consumption @ 75 % load: 2 l/h
 Autonomy @ 75 % load: 20 h
 Acoustic pressure: 95 dB(A)
 Length: 1357 mm
 Width: 707 mm
 Height: 942 mm
 Net weight: 350 Kg

Are you looking for a generating set with different technical characteristics? [HERE](#) you can find the area dedicated to generating sets of specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	8
Continuous power single phase (KW)	7.2
Maximum power single phase (KVA)	10
Continuous power single phase (KVA)	9
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x 230V 32A
Engine	Kubota D1105
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	1123
Number cylinders	3
Cooling	Water
Alternator	Synchronous
Protection degree	IP23

Motor insulation class	H
Fuel tank capacity (L)	40
Consumption (L/h)	2 at 75% of the load
Running time (h)	20 at 75% of the load
Acoustic power	95 dB(A)
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	1357
Width (mm)	707
Height (mm)	942
Dry weight (Kg)	350
Silenced	Yes
Super silenced	Yes
Product type	Generator
Voltage regulator	Capacitor
Engine manufacturer	Kubota