



## VITRIFRIGO C29D Portable Refrigerator-Freezers

Reference: FB1140380D

### VITRIFRIGO C29D PORTABLE FRIDGE-FREEZER

The VITRIFRIGO C29D is a portable fridge-freezer suitable for special installations, belonging to the C29D series with a digital thermostat.

This series is designed to adapt to various types of installations, both portable and fixed, such as dedicated compartments. The benefits of portability are embodied in three models with different capacities. Built with high-strength loaded polyethylene through rotational molding, these VITRIFRIGO C29D models offer maximum robustness, pleasant aesthetics, and efficiency.

The VITRIFRIGO fridge-freezers for special installations allow the creation of dedicated refrigerated compartments. Equipped with a practical removable container or sliding opening, they take up little space while maintaining good internal capacity.

The VITRIFRIGO C29D is equipped with a digital thermostat to allow precise temperature adjustment according to your needs. Furthermore, it is equipped with standard LED lighting, ensuring low consumption and high efficiency. The presence of standard handles facilitates the transport of portable fridges, while the fixing bracket ensures stability on various supports.

Other standard accessories include a practical internal basket with steel wires and a battery cable for battery power with a universal socket for the cigarette lighter.

In terms of technical specifications, the VITRIFRIGO C29D has a total capacity of 29 liters and a net weight of 15 kg. It operates on 12/24Vdc power, with a version also available that supports 100-240Vac 50/60Hz. Version D is only available with 12/24Vdc - 100-240Vac 50/60Hz power supply. The nominal power consumption is 48W.

The overall dimensions of the VITRIFRIGO C29D are width mm. 530, height mm. 390, depth mm. 345. The internal temperature range is from +10°C to -15°C, ensuring optimal preservation of food and beverages.

The VITRIFRIGO C29D is a versatile, durable, and efficient fridge-freezer, ideal for various applications, both portable and fixed, offering maximum convenience and flexibility.

#### Technical Specifications VITRIFRIGO C29D:

Total capacity litres: 29

Net weight: 15 Kg

Power supply: 12/24Vdc (also available 12/24Vdc - 100-240Vac 50/60Hz). D version only available 12/24Vdc - 100-240Vac 50/60Hz

Nominal consumption: 48W  
Total width: 530 mm.  
Total height: 390 mm.  
Total depth: 345 mm.  
Internal temperature range: +10°C / -15°C

Looking for a cockpit refrigerator with different technical characteristics? [Here](#) you can find the full range VITRIFRIGO or other specialized brands.

For more technical information, please refer to the attached datasheet.

The pictures and technical data are not binding and may be subject to revisions by the manufacturer.

\*\*\*

## Technical Sheet

Input power (W)	12/24Vdc (also available 12/24Vdc - 100-240Vac 50/60Hz). Version D only available 12/24Vdc - 100-240Vac 50/60Hz
Length (mm)	345
Width (mm)	530
Height (mm)	390
Dry weight (Kg)	15
Product type	Portable and special installation fridge-freezers
Capacity of the refrigerator (L)	29
Nominal consumption	48W
Internal temperature	+10°C / -15°C