



Vitrifrigo Seawater Pump 2200 Lt/h

Reference: WPPMD421.230/50

VITRIFRIGO SEAWATER PUMP 2200 LT/H

The VITRIFRIGO Seawater Pump, featuring "magnetic drive" technology, represents an advanced and reliable solution for the refrigeration and distribution needs on your yachts and boats. This VITRIFRIGO pump, part of the renowned MACS - Chiller Units and Accessories line, is carefully designed to ensure optimal performance and long-term reliability, providing a constant and uniform flow.

With a single-phase and 230V/1ph/50Hz power supply, this VITRIFRIGO pump absorbs only 0.38A of current, proving to be energy-efficient and ideal for prolonged use without concerns of overheating or overload. With an inlet and outlet of 20 mm, this VITRIFRIGO pump is capable of delivering an impressive flow of 2200 liters per hour, ensuring rapid and effective cooling of onboard systems, even on the hottest days.

The dimensions of the VITRIFRIGO, with a length of only 240 mm, a width of 120 mm, and a height of 130 mm - and a lightweight of 3.4 kg, make this pump characterized by a sturdy construction that makes it suitable for limited spaces onboard. Additionally, thanks to "magnetic drive" technology, this pump offers quiet and vibration-free operation, helping to maintain a comfortable and peaceful environment during navigation.

In conclusion, the VITRIFRIGO Seawater Pump is the ideal choice for anyone seeking high performance, reliability, and comfort aboard their vessels. With their advanced technology, innovative features, and robust construction, the VITRIFRIGO Seawater Pump ensures flawless operation and uniform distribution, contributing to enhancing the navigation experience and crew comfort.

Technical specifications VITRIFRIGO Seawater Pump:

Phase Type: Single-phase
Power supply: 230V/1ph/50Hz
Absorbed current: 0.38 A
Water inlet: 20 mm.
Water outlet: 20 mm.
Flow rate: 2200 lt/h
Length: 2400 mm.
Width: 120 mm.

Height: 130 mm.
Weight: 3.4 kg

Are you looking for a marine air conditioner? [HERE](#) you can find the area dedicated to Vitrifrigo marine air conditioners or other specialized brands.

Non-binding images and technical data.

Technical Sheet

| | |
|---------------------------------|---------------|
| Phase | Single phase |
| Maximum permissible current (A) | 0.38 |
| Length (mm) | 240 |
| Width (mm) | 120 |
| Height (mm) | 130 |
| Dry weight (Kg) | 3.2 |
| Feed Type | 230V/1ph/50Hz |
| Capacity (Lt/h) | 2200 |