



HYUNDAI GENERATOR THREE-PHASE SILENCED 40KW/50KVA STAGE II

Reference: 65529

HYUNDAI SILENT THREE-PHASE GENERATOR 40KW/50KVA STAGE II

HYUNDAI SILENT THREE-PHASE GENERATOR STAGE II 40KW/50KVA Silent power at your service

The Hyundai Three-Phase Stage II represents the ultimate expression of power and reliability in a single solution. Designed to meet the needs of individuals, businesses, and construction sites, this Hyundai generator offers a series of unbeatable benefits.

High-quality LK224D alternator: robust, reliable, and designed to provide a pure sine wave, it guarantees stable and safe power for all your devices, without the risk of damage.

Efficient and high-performance liquid cooling system: keeps engine temperature under control even in harsh working conditions, ensuring longer life, flawless operation, and overheating protection.

Deepsea DSE6120 control unit: a true cutting-edge control center, it allows you to monitor and manage all generator functions with maximum precision and ease. offering complete and intuitive control.

Technical features Hyundai Stage II Generator:

Phase type: Single-phase/Three-phase
 Maximum three-phase power: 55 KVA
 Continuous three-phase power: 50 KVA
 Maximum three-phase power: 44 KW
 Continuous three-phase power: 40 KW
 Fuel: Diesel
 Frequency: 50 Hz
 Voltage: 230/400 V
 Engine: YTO YTN4068-23N
 Starting: Electric
 Engine speed: 1500 rpm
 Tank capacity: 125 Lt
 Length: 247 cm
 Width: 101 cm
 Height: 112.5 cm
 Weight: 1204 Kg

If you are looking for a product similar to Hyundai Three Phase Generator click [HERE](#).

The image is purely indicative.

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	44

Continuous power three phase (KW)	
Maximum power three phase (KVA)	55
Continuous power three phase (KVA)	
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	YTN4068-23N
Emissions Regulations	Stage 2
Engine rpm (rpm)	1500
Starting system	Elettrico
Engine capacity (cm ³)	3620
Number cylinders	4
Cooling	Liquid
Alternator	LK224D
Protection degree	IP23
Fuel tank capacity (L)	125
Consumption (L/h)	13,3
Running time (h)	9,4
Acoustic pressure	85 dB(A) at 7 m
Length (mm)	2470
Width (mm)	1010
Height (mm)	1125
Engine manufacturer	YTO
Weight (Kg)	1204
Insulation Class	H/H