



VITRIFRIGO ND35 H2O Refrigeration unit

Reference: G5200090.002

VITRIFRIGO ND35 H2O REFRIGERATION UNIT

The VITRIFRIGO ND35 H2O refrigeration unit represents an advanced option for the construction of refrigerators and freezers up to 300 liters and 100 liters respectively. This device is powered as standard at 12/24 Vdc and comes with nitrogen pressure, ensuring effective refrigeration for a wide range of applications.

Refrigeration units are available following verification of compatibility with vessel dimensions and required power. Contact us for more information.

VITRIFRIGO ND35 H2O are designed with particular attention to quality and reliability, offering high-level performance in terms of energy efficiency and longevity. Their power flexibility allows them to be easily adapted to various electrical power requirements, providing a versatile solution for a variety of operational contexts.

With an optional 24V pump and a water flow rate of 12.5 liters per minute, the VITRIFRIGO ND35 H2O ensures efficient and uniform cooling, maintaining a constant temperature inside the refrigerated compartment. Thanks to its compact dimensions and optimized configuration, this device can be easily integrated into various environments without compromising performance.

Configuration options include the possibility of equipping the VITRIFRIGO ND35 H2O unit with quick couplings and an additional power supply option at 100/240 Vac, ensuring greater flexibility in installation and use. Furthermore, the availability of detailed tables with technical data provides a clear guide for configuring and practically applying this innovative system.

In conclusion, the VITRIFRIGO ND35 H2O represents an excellent choice for those seeking reliable and efficient performance in a wide range of refrigeration applications. Thanks to its build quality and versatility, this device stands out as a cutting-edge solution in the industrial refrigeration sector.

VITRIFRIGO ND35 H2O

Technical features of VITRIFRIGO ND35 H2O:

Standard equipment: 12/24Vdc without quick couplings (optional version 12/24Vdc - 100-240Vac 50/60Hz)
Optional equipment: 12/24Vdc - 100-240Vac 50/60Hz with quick couplings
24V pump: optional
Pump water flow rate: 12.5 l/min

Width: 290 mm.
Height: 170 mm.
Depth: 180 mm.
Pump width: 208 mm.
Pump height: 95 mm.
Pump depth: 160 mm.

VITRIFRIGO ND35 H2O

Looking for a product with different technical features? [Here](#) you can find the section dedicated to VITRIFRIGO refrigerating units or other specialized brands.

For more technical information, please refer to the attached datasheet.

Images are for illustration purposes only.

""

Technical Sheet

Length (mm)	180
Width (mm)	290
Height (mm)	170
Product type	Unità refrigerante
Standard equipment	12/24Vdc without quick couplings
Optional equipment	12/24Vdc - 100-240Vac 50/60Hz with quick couplings
Pump 24V	Optional
Pump water flow rate (lt/min)	12,5
Pump width (mm)	208
Pump height (mm)	95
Pump depth (mm)	160