



Generator Set With Automatic Panel 120KW Stage 5

Reference: 120KW STAGE 5

120KW WITH SILENCED THREE-PHASE AUTOMATIC PANEL HEATING UNIT Stage 5A

Technical characteristics of the 120KW ELECTRIC GENERATOR GROUP WITH SILENCED 3-PHASE PANEL Stage 5A:

Type of phase: three-phase

Three-phase emergency power: 132 KW / 165 KVA

Three-phase continuous power: 120 KW / 150 KVA

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: FPT NEF N67TEVP06.00

Motor speed: 1500 rpm

System type: Electric

Consumption: 50-75-100%- 17 - 24.6 - 32.8 l/h

Length: 3600 mm

Width: 1200 mm

Height: 2300 mm

Weight: 3070 kg

Silenced

Voltage regulator: AVR

Emission standards: Stage 5

if you are looking for a product similar to this [generator](#) click here.

Images and technical data are not binding.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	132
Continuous power three phase (KW)	120
Maximum power three phase (KVA)	165
Continuous power three phase (KVA)	150
Fuel	Diesel
Frequency (Hz)	50

Voltage (V)	400
Sockets configuration	Terminal box
Engine	FPT NEF N67TEVP06.00
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	6728
Number cylinders	6
Cooling	Water
Alternator	Self-excited, brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	104 x 132
Fuel tank capacity (L)	250
Consumption (L/h)	32.8 at 100% load
Running time (h)	14.4
Length (mm)	3600
Width (mm)	1200
Height (mm)	2300
AVR	Yes
Silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	FPT Iveco
Weight (Kg)	3070