

PRAMAC GBW15P APERTO CON QUADRO COMANDO AUTOMATICO

Reference: SH130TPAU02 /



The GBW series offers reliable and powerful machines, built for professional use in support of the power grid in case of blackouts or to serve isolated locations.

Easy to transport, install and position thanks to its compact size, this model is ideal for network emergency, construction, mobile workshops and industrial applications.

Available in open or hooded version.

YANMAR/PERKINS diesel engines
Water cooling
Industrial silencer
Fork base with trolleys
Motor fluids and charged battery

The images are purely indicative.

Technical Sheet

| | |
|------------------------------------|---------------------------------------|
| Phase | Three phase |
| Maximum power three phase (KW) | 11.28 |
| Continuous power three phase (KW) | 10.18 |
| Maximum power three phase (KVA) | 14.1 |
| Continuous power three phase (KVA) | 12.72 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 400 |
| Sockets configuration | 1 x 400V 32A 3P+N+T CEE |
| Engine | PERKINS 403D-15G, naturally aspirated |
| Speed governor | Mechanical |
| Starting system | Electric |
| Engine capacity (cm ³) | 1496 |
| Number cylinders | 3 |

| | |
|------------------------|--|
| Cylinders' position | In line |
| Oil capacity (L) | 6 |
| Cooling | Water |
| Alternator | Linz E1S13MD, with brushes |
| Poles | 4 |
| Fuel tank capacity (L) | 51 |
| Consumption (L/h) | 2.7 at 75% of the load / 3.6 at 100% of the load |
| Running time (h) | 18.6 at 75% of the load / 14.2 at 100% of the load |
| Length (mm) | 1600 |
| Width (mm) | 870 |
| Height (mm) | 950 |
| Dry weight (Kg) | 390 |
| Silenced | No |
| Super silenced | No |
| Product type | Generator |
| ATS Switch device | Optional ATS |
| Voltage regulator | Compound |
| Engine manufacturer | Perkins |