



## AMA Vertical Tank DTV DP 50 5K

Reference: AMA DTV DP 50 5K

### AMA DTV DP 50 5K

AMA DTV DP 50 5K double-walled, vertical-axis tank made of carbon steel EN 10025. The external protection tank has a holding capacity of 100% of the internal tank. The structure is supported by support skirts and lower bars that allow empty handling by forklift truck.

In accordance with the Ministerial Decree of 22/11/2017, the AMA DTV DP 50 5K tank does not require a containment basin and protection roof. The structure is easy to handle: it has eyebolts at the top for empty lifting and brackets at the bottom that allow it to be moved by forklift. DTV DPs are manufactured with capacities from 1,000 to 9,000 litres. From 3,500 l capacity, they are equipped with a side ladder for easy access to the manhole at the top.

Possibility of installing a wide range of dispensing units and distributors, in order to offer maximum versatility of use even for the most particular requirements. Predisposition for connection to management systems. All DTV DPs come with approved devices, CE marking and appropriate documentation. Equipped with a detection unit.

### Technical Sheet

Maximum output capacity (Lt/min)	50
Internal diameter (mm)	1900
Outer diameter (mm)	1930
Fuel tank capacity (L)	6000
Height (mm)	2490
Weight (Kg)	855
Voltaggio	230V