



PRAMAC GBW15P Generator Set Three-phase MCP 11.2KW Enclosure with manual control panel

Reference: SB130TPAY00

PRAMAC GBW15P THREE-PHASE MCP GENERATOR 11.2KW

PRAMAC GBW15P 11.2 kW three-phase generator with a diesel engine running at 1500 rpm. The PRAMAC GBW15P generator is equipped with an electric starter. The alternator of the PRAMAC GBW15P generator is a brushless, compound voltage regulator. The Perkins diesel engine makes the GBW15P generator very reliable, as it was built and designed using top-quality materials. Thanks to its canopy, this generator is super-silenced. Furthermore, its compact size makes it easy to transport, install, and position, making this model ideal for power grid emergencies, construction, mobile workshops, and industrial applications. The PRAMAC GBW15P three-phase generator is suitable for outdoor use on construction sites or for small professional jobs outdoors.

Technical characteristics of the PRAMAC GBW15P MCP Three-Phase generator:

Maximum power Three-Phase: 11.28 KW - 14.10 kVA

Continuous use power Three-Phase: 10.18 KW - 12.72 kVA

Fuel: Diesel

Voltage: 400 V

Frequency: 50 Hz

Engine: Perkins 403D-15G

Starting: Electric

Consumption: 3.6 Lt/h at 100% of load

Length: 1645 mm

Width: 870 mm

Height: 1072 mm

Weight: 550 Kg

Compound

Exhaust gas emission level: Not regulated

Sockets:

N.1 3P+N+T CEE 400V 32A

N.1 3P+N+T CEE 400V 16A

N.2 2P+T CEE 230V 16A

N.1 230V 16A SCHUKO

The PRAMAC GBW15P generator is a professional diesel generator developed by Pramac with the features and equipment needed to obtain a top-class product. Superior. The PRAMAC GBW15P generator, with its low noise level, is the ideal generator for use in residential areas or during non-working hours. The GBW15P generator is equipped with a reliable diesel engine, top-quality components, and comprehensive instrumentation. If you are looking for a generator like the PRAMAC GBW15P THREE-PHASE generator, we recommend browsing our catalog of [terrestrial generators](#) to find the one that best suits your needs.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	11.28
Continuous power three phase (KW)	10.18
Maximum power three phase (KVA)	14.1
Continuous power three phase (KVA)	12.72
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Emissions Regulations	Stationary Use
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	1496
Number cylinders	3
Cylinders' position	In line
Oil capacity (L)	6
Cooling	Water
Alternator	Linz E1S13MD, with brushes
Poles	4
Fuel tank capacity (L)	51
Consumption (L/h)	2.7 at 75% of the load / 3.6 at 100% of the load
Running time (h)	18.6 at 75% of the load / 14.2 at 100% of the load
Acoustic power	95 dB(A)
Acoustic pressure	66 dB(A) at 7 m
Length (mm)	1645
Width (mm)	870
Height (mm)	1072
Dry weight (Kg)	550
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Compound
Engine manufacturer	Perkins