



PRAMAC LIFTER SCALE TRUCK PY20

Reference: PY20

PRAMAC Lifter PY20 pallet truck scale

PRAMAC Lifter PY20 pallet truck scale is a hand pallet truck designed to efficiently and safely handle and weigh loads. Its features make it ideal for a wide range of applications in warehouses, workshops and other work environments.

Manual propulsion: The PY20 is manually driven, making it an economical and environmentally friendly choice. It requires no batteries or recharging, so it is always ready for use.

Accompanying drive system: This system allows the operator to steer the truck by pushing or pulling it by hand. It is ideal for manoeuvring

in tight spaces and for precise load control.

2000 kg capacity: The PY20 has a maximum capacity of 2000 kg, making it capable of handling heavy loads with ease.

4 Rear Wheels: The four rear wheels provide stability and safety when handling loads.

2 Front Wheels: The two front swivel wheels facilitate manoeuvrability and allow the trolley to swivel in tight spaces.

Lifting height 120 mm: The PY20 can lift loads up to a height of 120 mm, making it easier to load and unload trucks or trailers.

Compact Dimensions: With an overall length of 1640 mm, an overall width of 540 mm and a fork width of 540 mm, the PY20 is a compact truck that easily adapts to any working environment.

Fork length 1150 mm: The 1150 mm long forks allow long and bulky loads to be handled.

Stowage aisle 1678 mm: The 1678 mm stowage aisle allows the PY20 to operate in narrow aisles.

Vault radius 1350 mm: The 1350 mm turning radius facilitates manoeuvrability of the truck in tight spaces.

Integrated weighing function: The PY20 has an integrated weighing function that allows loads to be weighed directly on the truck.

This eliminates the need for a separate scale, saving time and increasing efficiency.

Main technical characteristics of the PRAMAC Lifter PY20 pallet truck scale:

Drive type: Manual

Drive system: Accompaniment

Load capacity: 2000 kg

Quantity of rear wheels: 4
Number of front wheels: 2
Lifting height: 120 mm
Total length: 1640 mm
Total width: 540 mm
Fork width: 540 mm
Fork length: 1150 mm
Stowage aisle: 1678 mm
Turning radius: 1350 mm

If you are looking for another kind of product for the transport and storage of goods, then you can [consult our catalogue with a large selection of products.](#)

Images and technical data are not binding.

Technical Sheet

Drive	Manual
Operator type	Pedestrian
Load capacity (Kg)	2000
Load centre distance (mm)	600
Load axle to end forks (mm)	938
Wheel base (mm)	1260
Service weight (Kg)	99
Axle load, laden rear (Kg)	629
Axle load, laden front (Kg)	1470
Axle load, unladen front (Kg)	62
Axle load, unladen rear (Kg)	37
Tyres: front wheels	POLY
Tyres: rear wheels	POLY
Diameter steering wheels (mm)	180
Width steering wheels (mm)	50
Diameter load rollers (mm)	70
Width load rollers (mm)	50
Lift height (mm)	120
Overall length (mm)	1640
Overall width (mm)	540
Weight (Kg)	99