



GYS MULTIWELD 200M SALDATRICE MIG - MAG Inverter

Reference: 066595

GYS MULTIWELD 200M MIG - MAG Inverter WELDING MACHINE

GYS MULTIWELD 200M is a high-performance single-phase inverter welding machine designed to meet the MIG/MAG, flux-cored wire and MMA needs of hobbyists and professionals. Equipped with an intuitive interface, precise unwinding system and advanced technologies, this machine guarantees flawless welding results on a variety of materials, including aluminium.

Key features GYS MULTIWELD 200M:

GYS MULTIWELD 200M Welding processes: MIG/MAG (steel wire, stainless steel, aluminium), flux cored wire (reverse polarity), MMA (basic and rutile electrodes up to Ø 4 mm)

Manual adjustment of arc dynamics: For precise control of arc stability and welding quality.

GYS Welding aid: Table on the front panel for easy setting of tension and wire diameter according to the thickness of the material to be welded.

GYS Intuitive interface: Digital screens that can be read even in bright sunlight, buttons and knobs suitable for grooved hands for simple and convenient operation.

4-roller unrolling system: Compatible with wire coils Ø 200/300 mm, ensures smooth and even wire unrolling.

GYS MULTIWELD 200M Powerful wire feeder: Ensures constant wire feed for precise, uninterrupted welding.

GYS MULTIWELD 200M European torch connection: Quick and safe torch assembly/disassembly.

GYS Compatible electrical sockets: US (type A) and EURO (types C/E/F) for greater flexibility.

GYS MULTIWELD 200M Pre-installed socket for gas heater: For welding under pure CO₂ (heater not included).

GYS MULTIWELD 200M Sturdiness and portability: Reinforced wheels for stability and manoeuvrability, holder for gas cylinders up to 4 m³ (20L).

GYS MULTIWELD 200M MIG - MAG Inverter WELDING MACHINE: The ideal choice for those looking for a versatile, high-performance and easy-to-use welding machine. Perfect for maintenance, repair and construction work in the workshop, construction site or for hobby use.

Technical specifications GYS MULTIWELD 200M:

Supply voltage: 230 V

Mains frequency: 50/60 Hz

Adjustable welding current (MIG & MAG):

230V - I2 MMA: 30 - 180A

230V - I2 MIG: 30 - 200A

Reference standards:

EN 60974-1 (40°C) for MIG

EN 60974-1 (40°C) for MAG

Weight: 34.5 Kg

Degree of protection: IP 21

Product dimensions: 770 x 790 x 470 mm

Absorbed power: 9 Kw

MACHINE THICKNESS

GAS in 230V: 0.6

NO GAS in 230V: 1.2

Electronic Control: Automatic

Looking for a portable welding machine with different features? [Here](#) you can find the whole range of GYS or other specialized brands

Images and technical data are not binding and may be subject to revision by the supplier

Technical Sheet

Phase	Single phase
Frequency (Hz)	50 / 60
Voltage (V)	230
Protection degree	IP21
Product dimensions (mm)	770 x 790 x 470
No-load voltage (V)	65
Regulation current (A)	230V in I2 MMA: 30 - 180A / 230V in I2 MIG: 30 - 200A
Type of welding	MIG-MAG
Weight (Kg)	34.5
EN 60974-1 (40°C) 230V	MIG-MAG: IA (60%): 115 A 100%: 90A / MMA IA (60%): 104 A 100%: 80 A