

FENZI G5 Tank 1500LT

Reference: G5 16R000



FENZI G5 Cistern 1500LT

FENZI G5 Cistern 1500LT

FENZI G5 Cistern 1500LT: Complete solution for the safe storage of diesel fuel

The FENZI G5 1500LT is an above-ground diesel tank designed to meet the needs of heating and powering generator sets. Made in compliance with Italian regulations (DM 31/07/1934, DM 28/04/2005, DM 13/07/2011 and DM 22/11/2017), it offers a complete and safe solution for storing diesel fuel.

Fenzi materials:

Fenzi Cistern: the heart of the system, where diesel fuel is stored safely and reliably.

110% containment basin: capable of retaining the entire contents of the tank in the event of a spillage, guaranteeing maximum environmental safety.

Fenzi: 90% load limiting valve: prevents overloading of the tank, preventing accidents and damage.

External float level indicator: makes it easy to monitor the level of residual diesel fuel in the Fenzi tank.

Fenzi: Manhole Ø 420 mm: easy access for inspection and maintenance inside the tank.

Eyebolts for vacuum lifting: facilitate transport and positioning of the Fenzi tank.

Unloading sleeve for cleaning: allows the tank to be easily emptied for cleaning and maintenance.

Earthing socket and equipotential bonding: ensures the electrical safety of the system.

External 1" suction connection with non-return valve: enables quick and safe withdrawal.

1" ball valve: regulates the flow in and out of the tank.

1" galvanised steel pipe with flexible end piece: connects the cistern to the diesel delivery system.

Fenzi safety:

110% containment basin to retain any leaks

Drain sleeve for water collection

Venting funnel with flame breaker mesh

Compliance with Italian regulations

Technical characteristics Fenzi Tank 1500LT

Capacity: 1500LT

Length: 2300 mm

Width: 1300 mm

Height: 2100 mm

Intake Inches: 1"

If you are looking for a product like FENZI G5 1500LT Cistern with different characteristics, check out [HERE](#).

Images and data purely indicative.

Technical Sheet

Tank capacity (L)	1000
Length (mm)	2000
Width (mm)	1200
Height (mm)	2100
withdrawal inches	1"