Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

FENZI G5 Tank 2300LT

Reference: G5 20R000

FENZI G5 Cistern 2300LT

FENZI G5 Cistern 2300LT

FENZI G5 Cistern 2300LT is an above-ground cistern for diesel fuel designed to meet the storage needs of large volumes of diesel fuel for heating and powering generator sets.

Built in compliance with Italian regulations (DM 31/07/1934, DM 28/04/2005,

DM 13/07/2011 and DM 22/11/2017), it offers a complete, efficient and safe solution for the storage of diesel in industrial and commercial contexts.

Fenzi High quality materials for excellent robustness and strength:

Fenzi: painted steel plate for superior protection against corrosion and weathering.

Containment basin: painted carbon steel EN10025 S235JR for maximum safety in case of accidental spills.

Canopy (optional): non-combustible material, galvanised frame and galvanised trapezoidal sheet metal for a solid and durable structure that withstands the elements.

Complete components for safe and practical operation:

110% containment basin: capable of retaining the entire contents of the Fenzi tank in the event of a spill, guaranteeing maximum environmental protection.

90% load limiting valve: prevents overloading of the tank, preventing accidents and damage.

External float level indicator: allows the level of residual diesel fuel in the 2300LT tank to

Manhole Fenzi Ø 420 mm: easy access for inspection and maintenance inside the tank.

Eyebolts for vacuum lifting: facilitate transport and positioning of the tank.

Drain sleeve for cleaning: allows easy emptying for cleaning and maintenance.

Earthing socket and equipotential bonding: ensures the electrical safety of the system.

External 1" suction connection with non-return valve: allows quick and safe removal of diesel fuel.

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Fenzi 1" ball valve: regulates the flow of diesel fuel in and out of the tank.

Fenzi 1" galvanised steel pipe with flexible terminal: connects the tank to the diesel fuel delivery system.

Technical specifications Fenzi Tanks G5 2300LT:

Capacity: 2300LT
Length: 2400 mm
Width: 1500 mm
Height: 2200 mm
Intake Inches: 1"

If you are looking for a product like FENZI G5 2300LT Cistern with different characteristics, check out HERE.

Images and data purely indicative.

Technical Sheet

Tank capacity (L)	2300
Length (mm)	2400
Width (mm)	1500
Height (mm)	2200
withdrawal inches	1"