

## PRAMAC GSL30D COFANATO CON QUADRO COMANDO MANUALE

Reference: SU290TDAT00 /



Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	25.55
Continuous power three phase (KW)	24.31
Maximum power three phase (KVA)	31.94
Continuous power three phase (KVA)	30.39
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 63A 3P+N+T - 1 x 400V 32A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine	Deutz AG F4M2011, naturally aspirated
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	3110
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	10
Cooling	Oil
Alternator	Mecc Alte ECP28-VL/4, brushless
Poles	4

Fuel tank capacity (L)	68
Consumption (L/h)	5.7 at 75% of the load / 8 at 100% of the load
Running time (h)	11.9 at 75% of the load / 8.4 at 100% of the load
Acoustic power	89 dB(A)
Acoustic pressure	60 dB(A) at 7 m
Length (mm)	2005
Width (mm)	948
Height (mm)	1308
Dry weight (Kg)	760
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Deutz