

PRAMAC GSL30D COFANATO CON QUADRO COMANDO AUTOMATICO

Reference: SU290TDAT02 /



Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

Technical Sheet

| | |
|------------------------------------|---------------------------------------|
| Phase | Three phase |
| Maximum power three phase (KW) | 25.55 |
| Continuous power three phase (KW) | 24.31 |
| Maximum power three phase (KVA) | 31.94 |
| Continuous power three phase (KVA) | 30.39 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 400 |
| Sockets configuration | 1 x 400V 63A 3P+N+T CEE |
| Engine | Deutz AG F4M2011, naturally aspirated |
| Speed governor | Mechanical |
| Starting system | Electric |
| Engine capacity (cm ³) | 3110 |
| Number cylinders | 4 |
| Cylinders' position | In line |
| Oil capacity (L) | 10 |
| Cooling | Oil |
| Alternator | Mecc Alte ECP28-VL/4, brushless |
| Poles | 4 |
| Fuel tank capacity (L) | 68 |

| | |
|---------------------|---|
| Consumption (L/h) | 5.7 at 75% of the load / 8 at 100% of the load |
| Running time (h) | 11.9 at 75% of the load / 8.4 at 100% of the load |
| Acoustic power | 89 dB(A) |
| Acoustic pressure | 60 dB(A) at 7 m |
| Length (mm) | 2005 |
| Width (mm) | 948 |
| Height (mm) | 1308 |
| Dry weight (Kg) | 760 |
| Silenced | Yes |
| Super silenced | Yes |
| Product type | Generator |
| ATS Switch device | Optional ATS |
| Voltage regulator | AVR |
| Engine manufacturer | Deutz |