



PRAMAC GSL42D

Reference: PRAMAC GSL42D

Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	35.62
Continuous power three phase (KW)	33.85
Maximum power three phase (KVA)	44.52
Continuous power three phase (KVA)	42.31
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	Deutz AG BF4M2011, turbo
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	3110
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	10
Cooling	Oil
Alternator	Mecc Alte ECO/P32-3S/4, brushless
Poles	4
Fuel tank capacity (L)	91
Consumption (L/h)	8.1 at 75% of the load / 11.2 at 100% of the load

Running time (h)	11.3 at 75% of the load / 8.1 at 100% of the load
Length (mm)	1800
Width (mm)	750
Height (mm)	1518
Dry weight (Kg)	761
Silenced	No
Super silenced	No
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Deutz