

GENSET SILENCED 33 KVA



Reference: GES33KVA

GENSET SILENCED 33 KVA

SILENCED GENERATOR 33 KVA: Power and Reliability at your fingertips

The SILENCED GENERATING UNIT 33 KVA is a powerful electric generator designed to provide reliable and silent emergency or continuous power. With a maximum output of 33 kVA and a Baudouin 4M06G35/5 diesel engine, this generator set is the ideal solution for a wide range of applications, both domestic and industrial.

Key features:

Powerful and reliable: The Baudouin diesel engine ensures high performance and a long service life.

Quiet: Thanks to its soundproof housing, the noise level at 7 metres is only 70 dB(A), ensuring discrete operation.

Versatile: The 230V/400V output voltage and 50 Hz frequency make it compatible with most household appliances and equipment.

Autonomy: The 100-litre tank guarantees a long operating autonomy.

Compact dimensions: With its small size (2100x870x1165 mm), it can be easily transported and installed.

Low emissions: The engine complies with emission regulations, respecting the environment.

Technical characteristics SILENCED ELECTROGEN GROUP 33 KVA:

Type of phase: Three-phase

Three-phase continuous power: 24 kW

Three-phase continuous power: 30 kVA

Maximum three-phase LTP power: 26.4 kW

Maximum three-phase LTP power: 33 kVA

Fuel: Diesel

Voltage: 230V/400V

Frequency: 50 Hz

Manufacturer and type: Baudouin 4M06G35/5
1500 rpm

Displacement: 2300 cc.

Alternator MECC ALTE ECP28-VL4 4 poles

Noise level at 7 m: 70 dB(A)

Tank: 100 Lt.

Length: 2100 mm

Width: 870 mm
 Height: 1165 mm
 Dry weight: 940 Kg. approx.
 Emission level: not emitted

If you are looking for a product with similar characteristics [CLICK HERE](#).

Non-binding images and technical data.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	26.4
Continuous power three phase (KW)	24
Maximum power three phase (KVA)	33
Continuous power three phase (KVA)	30
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	Baudouin 4M06G35/5
Emissions Regulations	Not Emitted
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	2300
Number cylinders	4
Alternator	MECC ALTE ECP28-VL/4
Poles	4
Protection degree	IP23
Motor insulation class	H
Fuel tank capacity (L)	100
Consumption (L/h)	5.61 at 75% of the load
Acoustic pressure	70 dB(A) at 7 m
Length (mm)	2100
Width (mm)	870
Height (mm)	1165
Dry weight (Kg)	940
Silenced	Yes
ATS Switch device	Optional ATS

Engine manufacturer

Baudouin
