



## VISA F105GXLVM-IM SILENCED GENSET 100 KVA STAGE V

Reference: F105GXLVM/IM

### VISA F105GXLVM-IM SILENCED GENSET 100 KVA STAGE V

VISA Genset F105GXLVM-IM is a state-of-the-art three-phase genset designed to provide a reliable and silent power supply, even under the most demanding conditions. With a continuous power output of 80 kW and an FPT-IVECO F36ETVP03 engine that complies with Stage V emissions regulations, this genset is the ideal solution for a wide range of applications, in both industrial and civil applications.

#### **Key features** VISA Genset F105GXLVM-IM:

**Powerful and reliable:** The FPT-IVECO F36ETVP03 4-cylinder engine ensures high performance and a long service life.

**Quiet:** Thanks to the Visa silencer model, the noise level is extremely low, ensuring discrete operation.

**Versatile:** The 400 V output voltage and 50 Hz frequency make it compatible with most electrical appliances.

**Economical:** Its low consumption of 20.8 litres/hour at 75% load makes it a cost-effective solution.

**Robust:** The solid construction and high-quality components guarantee a long service life.

**Environmentally friendly:** Compliant with Stage V emissions regulations.

#### **Why choose the** VISA Genset F105GXLVM-IM?

**Construction:** Ideal for powering construction equipment and lighting.

**Agriculture:** Perfect for powering agricultural machinery and irrigation systems.

**Events:** Suitable for powering sound systems, lighting and other equipment during outdoor events.

**Industry:** Provides emergency or continuous power for production processes.

#### Socket version:

SOCKET KIT NI-01: standard version

PRESE KIT NI-05: version consisting of

a watertight box mounted on the genset that includes

1 125A +3pole+N+E EEC socket protected by circuit breaker,

1 x 63A +3pole+N+E CEE socket protected by circuit breaker +

RCCB (30mA, TYPE A), 1 x 32A CEE socket +3poles+N+E

protected by dedicated circuit breaker + RCCB (30mA TYPE A)  
 1x 16A +3poles+N+E EEC socket protected by circuit breaker +  
 RCCB (30mA TYPE A) 1x 16A single-phase Schuko CEE socket protected by circuit breaker  
 + RCCB (30mA TYPE A). Neutral connection to earth.

**By choosing the NI-05 Socket Kit version, the Standard Kit version NI-01 will not be present.**

**Technical characteristics** VISA Genset F105GXLVM-IM:

Phase type: Three-phase  
 Three-phase continuous power: 100 KVA  
 Three-phase continuous power: 80 KW  
 Voltage: 400 V  
 Frequency: 50 Hz  
 Motor: FPT-IVECO - F36ETVP03  
 Engine speed: 1500 rpm  
 Starting: Electric  
 Consumption: 20.8 Lt/h at 75% load  
 Length: 3060 mm  
 Width: 1200 mm  
 Height: 2200 mm  
 Fuel tank: 360 L  
 Supersilenced  
 Number of cylinders: 4  
 Cooling: Water  
 Electronic Regulator: Standard  
 Stage V  
 Silencer Model: Visa  
 sound pressure: 65dBA(+/-3)@7m

If you are looking for a product such as the VISA then you can browse the entire VISA [generator](#) range or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

**Technical Sheet**

Phase	Three phase
Continuous power three phase (KW)	80
Continuous power three phase (KVA)	100
Frequency (Hz)	50
Voltage (V)	400
Engine	FPT-IVECO - F36ETVP03
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	3600
Number cylinders	4
Cooling	Water
Tank capacity (L)	360

Consumption (L/h)	at 75% (P.R.P.) 20.8 l/h
Acoustic pressure	65 dB(A) at 7 m
Length (mm)	3060
Width (mm)	1200
Height (mm)	2200
Silenced	Yes
Product type	Generator
Engine manufacturer	FPT Iveco