



TRUMA COMBI Gas 4000W - 12V with iNET-X control and electric heater 1800W

Reference: 010 C4E-INETX-G

TRUMA COMBI Gas 4000W - 12V with iNET-X control and electric heater 1800W

TRUMA Combi Gas 4000W - 12V: Comfort at your fingertips, wherever you are

The TRUMA Combi Gas 4000W is a state-of-the-art combi heater, designed to provide maximum comfort

in your motor home or caravan. Thanks to its versatility and outstanding performance

this device is the ideal solution for quickly and efficiently heating both your indoor environment and domestic water.

Key features:

Hybrid heating: Combines the power of propane/butane gas with the convenience of 12V electric heating, allowing you to use it in any situation, even when you are away from a power outlet.

Powerful and fast: With a nominal heat output of 4000W gas and 1800W electric, it heats the room and water quickly, providing you with maximum comfort in no time.

Efficient: Thanks to its high energy efficiency, it consumes little fuel and ensures economical operation.

Compact and light: With its small dimensions (510x450x300mm) and weight of only 15.5kg, it is easy to install and transport.

Easy to use: The iNET-X control allows you to control the heater intuitively and conveniently, directly from your smartphone.

Safe: Equipped with numerous safety features, it guarantees safe and reliable operation.

Technical Specifications TRUMA Combi Gas 4000W:

Type of power supply: Propane / butane + electric

Operating pressure: 30 mbar

Nominal heat output gas operation: 2000 W / 4000 W

Nominal heat output electrical operation: 900 W / 1800 W

Nominal heat output mixed operation: max. 3800 W

Fuel consumption: 160 - 335 g/h

Current consumption (at 12 V): heating and water tank operation

for short time max. 6.5 A (average approx. 1.2 A)

Current consumption (at 230 V) 3.9 A / 7.8 A

Capacity 10 litres

Heating time (from approx. 15 °C to approx. 60 °C): Water tank approx. 23 min.

Heating time (from approx. 15 °C to approx. 60 °C): Heating and water tank according to EN 15033 approx. 80 min.

Weight (without peripherals) approx. 15.5 kg
Dimensions (W x D x H): 510 x 450 x 300 mm

If you are looking for a product with similar characteristics [CLICK HERE](#).

Picture and technical data purely indicative.

Technical Sheet

Fuel	Gas
Pressure (bars)	30
Tank capacity (L)	10
Max rated heat power	4000W
Min rated heat power	2000W
Air flow (m ³ /h)	287
Length (mm)	510
Width (mm)	450
Height (mm)	300
Weight (Kg)	15.5
Consumo	160 – 335 g/h
Nominal heat output electrical operation	900 W / 1800 W
Rated thermal output mixed operation	3800 W