

PRAMAC GSW115P COFANATO CON QUADRO COMANDO MANUALE

Reference: SU121TPAX00



Technical Sheet

Phase	Three phase
Continuous power three phase (KW)	84.92
Maximum power three phase (KVA)	116
Continuous power three phase (KVA)	106.15
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	PERKINS 1104D-E44TAG2, turbocharged
Emissions Regulations	Stage 3A
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	4400
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	8
Cooling	Water
Alternator	Mecc Alte ECP34-2S/4, brushless
Poles	4
Fuel tank capacity (L)	209
Consumption (L/h)	17 at 75% of the load / 24.7 at 100% of the load
Running time (h)	12.3 at 75% of the load / 8.4 at 100% of the load

Acoustic power	96 dB(A)
Acoustic pressure	67 dB(A) at 7 m
Length (mm)	2400
Width (mm)	1000
Height (mm)	1685
Dry weight (Kg)	1500
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Perkins