



TRUMA - Vario Heat eco heater with CP-PLUS iNET Ready control

Reference: 010 VHC-CP

TRUMA - Vario Heat comfort heater with CP-PLUS iNET Ready control

The Truma Vario Heat comfort is a gas heater designed specifically for vans

motor homes and caravans. Belonging to the new generation of Truma heaters, it is characterised by its power, compactness and ease of use.

Key features:

Customisable power: Thanks to the three power levels (1300W, 2800W, 3700W), you can adapt the heating to your needs, whether you want a warm and cosy environment or simply to eliminate humidity.

Fast heating: The Boost function significantly increases the air flow, allowing your vehicle to heat up in record time.

Digital control: The CP plus VarioHeat digital control panel gives you precise and intuitive temperature control.

Compact and efficient: The compact and lightweight design makes it easy to install, while the high energy efficiency reduces gas consumption.

Silent operation: Night mode ensures near-silent operation, ideal for a peaceful night's rest.

iNET X compatibility: Although not specified in the technical specifications provided, the VarioHeat comfort is likely to be compatible with the iNet X system, allowing you to control the heating remotely via app. This feature, suggested by the key phrase, adds value to the product.

Technical characteristics Vario Heat comfort Stove:

Type of power supply: Propane - butane
Operating pressure: 30 mbar
Nominal heat output
Power: 1300W - 2800W - 3700W
Fuel consumption
100 g/hour - 220 g/hour - 290 g/hour
Voltage supply: 12 V
Current consumption 0.65A / 2.75A / 5.4A
Weight 5.5 kg
Dimensions: 400 x 284 x 123 mm
Air flow rate (free discharge)
75 m³/hour / 155 m³/hour / 210 m³/hour

Quiescent current consumption CP plus Vario Heat - 4mA

If you are looking for a product with similar characteristics [CLICK HERE](#).

Picture and technical data purely indicative.

Technical Sheet

Voltage (V)	12
Pressure (bars)	30
Max rated heat power	3700
Min rated heat power	1300
Air flow (m ³ /h)	(free discharge) 75 m ³ /hour / 155 m ³ /hour / 210 m ³ /hour
Length (mm)	400
Width (mm)	284
Height (mm)	123
Weight (Kg)	5.5
Consumo	100 g/hour / 220 g/hour / 290 g/hour