



CUMMINS C2250D5 Open Generator Three Phase 2250KVA Diesel

Reference: C2250D5

CUMMINS C2250D5 Open Generator Three Phase 2250KVA Diesel

CUMMINS C2250D5 is a powerful three-phase electric generator, designed to provide reliable and continuous power in large industrial and commercial applications. This generator is ideal for ensuring power supply in critical situations, such as emergencies or as a primary power source in isolated plants.

Key Features:

Power: With a maximum power of 2250 kVA and a continuous power of 2000 kVA, this generator is able to power a wide range of electrical equipment, even under high load conditions.

Engine: Equipped with a robust Cummins QSK60-G4 diesel engine, synonymous with reliability and durability. This engine is known for its efficiency and its ability to operate in harsh environmental conditions.

Voltage and Frequency: Provides a voltage of 400-440 V and a frequency of 50 Hz, suitable for most industrial and commercial applications.

Dimensions and weight: With dimensions of 6175 mm x 2286 mm x 2537 mm and a dry weight of 16404 kg, this generator is of considerable size, but offers a lot of power.

Consumption: The fuel consumption is 328 litres per hour at 75% load, a value in line with the performance of the generator and its power.

Electric start: The electric start makes starting the generator quick and easy.

Electronic speed governor: Ensures precise regulation of frequency and voltage.

Technical Features:

Phase type: Three-phase
Continuous power: 2000 KVA / 1600 KW
Maximum power: 2250 KVA / 1800 KW
Engine: Cummins QSK60-G4
Power supply: Diesel
Engine speed: 1500 rpm
Starting: Electric
Speed ??governor: Electronic
Voltage: 400-440 V
Frequency: 50 Hz

Consumption at 75% load: 328 l/h
Length: 6175 mm
Width: 2286 mm
Height: 2537 mm
Dry weight: 16404 kg

If you are looking for a product similar to CUMMINS C2250D5 with similar features [CLICK HERE](#).

Images and technical data are purely indicative.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	1800
Continuous power three phase (KW)	1600
Maximum power three phase (KVA)	2250
Continuous power three phase (KVA)	2000
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400 - 440
Engine rpm (rpm)	1500
Starting system	Electric
Consumption (L/h)	328 at 75% load
Length (mm)	6175
Width (mm)	2286
Height (mm)	2537
Dry weight (Kg)	16404
Engine manufacturer	Cummins