

Generator set 66KVA Silent Stage II



Reference: GEGP66SY

Generator set 66KVA Silent Stage II

66KVA Silent Stage II Generator - Power and Reliability

This three-phase generator is the ideal solution for providing emergency or continuous power supply in various industrial and commercial applications. With a maximum power of 66 KVA and a continuous power of 60 KVA, this generator is capable of powering a wide range of electrical equipment, even under high load conditions.

Main features:

Powerful engine: Equipped with a robust FPT N45SM1A diesel engine, synonymous with reliability and durability.

Regulatory compliance: Complies with Stage II emissions regulations, ensuring low environmental impact.

Silence: Thanks to the soundproofing system, the noise level is reduced, allowing use in noise-sensitive environments.

Compact and easy to handle: With small dimensions (2260x1000x1420 mm) and a weight of 1250 kg, it is easy to transport and install.

Autonomy: The 100-liter tank guarantees adequate autonomy for many applications.

Protection: The IP23 protection rating ensures good resistance to dust and water splashes.

Electric start: The electric start makes starting the generator quick and easy.

Technical Features:

Maximum three-phase power: 66 KVA

Continuous three-phase power: 60 KVA

Maximum three-phase power: 53 KW

Continuous three-phase power: 48 KW

Fuel: Diesel

Voltage: 230/400 V

Engine: FPT N45SM1A

Protection rating: IP23

Start: Electric

Tank capacity: 100 lt.

Length: 2260 mm

Width: 1000 mm

Height: 1420 mm

Weight: 1250 Kg

If you are looking for a product with similar characteristics [CLICK HERE](#).

Images and technical data are purely indicative.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	53
Continuous power three phase (KW)	48
Maximum power three phase (KVA)	66
Continuous power three phase (KVA)	60
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	FPT N45SM1A
Emissions Regulations	Stage 2
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	4500
Number cylinders	4
Cylinders' position	In line
Protection degree	IP23
Fuel tank capacity (L)	100
Consumption (L/h)	13.3 at 75% Load
Running time (h)	10.2
Acoustic pressure	65 dB(A) at 7 m
Length (mm)	2260
Width (mm)	1000
Height (mm)	1420
Dry weight (Kg)	1250
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR