

PRAMAC GSW140I HOOD WITH MANUAL CONTROL PANEL (MCP)

Reference: SU121TCAY00



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	140.21
Continuous power three phase (KW)	101.97
Maximum power three phase (KVA)	140.21
Continuous power three phase (KVA)	127.46
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	FPT NEF67SM1A, turbocharged
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	6
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	17.2
Cooling	Water
Alternator	Mecc Alte ECP34-1L, brushless
Poles	4
Fuel tank capacity (L)	350
Consumption (L/h)	21.5 at 75% of the load / 28.2 at 100% of the load
Running time (h)	16.2 at 75% of the load / 12.4 at 100% of the load

Acoustic power	97 dB(A)
Acoustic pressure	68 dB(A) at 7 m
Length (mm)	3400
Width (mm)	1250
Height (mm)	1770
Dry weight (Kg)	1995
Inverter	No
AVR	Yes
Compound	No
Silenced	Yes
Super silenced	Yes