



## ITALTOWER Street-PRO02 Light Tower 4x160W MultiLED

Reference: STREET\_PRO02

### ITALTOWER Street-PRO02 4x160W MultiLED Tower Light

ITALTOWER Street-PRO02 4x160W MultiLED Tower Light: Powerful and versatile lighting

ITALTOWER Street-PRO02 is a professional light tower designed to provide intense and uniform lighting in all conditions. Thanks to its 4 x 160W LED projectors, this tower is able to illuminate an area of up to 2400 square metres, providing excellent visibility even in the darkest areas.

#### Key Features:

**Robust construction:** Made of galvanised steel, the tower is corrosion and weather resistant, ensuring a long lifespan.

**Flexibility:** The telescopic galvanised steel pole allows the height of the tower to be adjusted up to 5.5 metres, adapting it to any requirement.

**Energy efficiency:** Energy-efficient LED floodlights ensure a long service life and reduce running costs.

**Transportability:** Thanks to its compact closed dimensions (1200x800x2000 mm) and fixed trolley, the tower is easy to transport and position.

**Stability:** The tower is equipped with a stabilisation system that makes it safe even in high wind conditions up to 80 km/h.

#### Technical characteristics:

Phase type Single-phase

Frequency (Hz) 50

Type of LED lamps

Telescopic pole Galvanised steel

Illuminated area (m<sup>2</sup>) 2400

Total lumens (Lm) 87680

Lifting system Manual lifting system

Maximum height (m) 5.5

Dimensions open (mm) 1200 x 1291 x 5500

Dimension closed (mm) 1200 x 800 x 2000

Wind stability (Km/h) 80

Weight (Kg) 260

trolley: Stationary

Are you looking for a product with different characteristics? [HERE](#) you can find the entire range of ITALTOWER lighting towers or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the supplier.

## Technical Sheet

Phase	Single phase
Type of lamps	LED
Telescopic pole	Galvanized steel
Total lumens (Lm)	87680
Lifting System	Manual lifting system
Open size (mm)	1200 x 1291 x 5500
Closed size (mm)	1200 x 800 x 2000
Stability to wind (Km/h)	80 Km/h
Weight (Kg)	260
Operating temperature range (°C)	-30/+50
carello	Stazionaria