



## PRAMAC GSW150V COFANATO CON QUADRO COMANDO AUTOMATICO

Reference: SU141TWAU02

### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	116.13
Continuous power three phase (KW)	104.05
Maximum power three phase (KVA)	145.16
Continuous power three phase (KVA)	130.06
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	VOLVO TAD532GE, turbo intercooled
Emissions Regulations	Stage 2
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	4760
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	13
Cooling	Water
Alternator	Mecc Alte ECP34-1L, brushless
Poles	4
Fuel tank capacity (L)	350
Consumption (L/h)	21.9 at 75% of the load / 29.5 at 100% of the load

Running time (h)	16 at 75% of the load / 11.8 at 100% of the load
Acoustic power	97 dB(A)
Acoustic pressure	68 dB(A) at 7 m
Length (mm)	3000
Width (mm)	1150
Height (mm)	1760
Dry weight (Kg)	1720
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Volvo