



WhisperPower MCC 24-12 VDC 5A B2B battery charger

Reference: 60201023

WhisperPower MCC 24-12 VDC 5A B2B charger

The WhisperPower MCC 24-12 VDC 5A B2B is a high-quality electronic device designed to efficiently and safely convert 24 Volts to 12 Volts. This converter is ideal for a wide range of applications, such as motorhomes, boats, commercial vehicles and off-grid power systems.

Key features:

Efficient conversion: Converts voltage from 24V to 12V with over 92% efficiency, minimising energy losses.

Intelligent battery charging: Uses a three-stage charging process, ensuring fast, efficient and safe charging of 12V batteries.

Built-in protections: Features protections against short circuits, overcharging and overheating, ensuring long life and safe operation.

Voltage regulation: Allows the output voltage to be adjusted between 12V and 15V, adapting to different needs.

Temperature sensor: The integrated temperature sensor allows the internal temperature to be monitored and the operation of the converter to be adjusted accordingly.

Dimming function: Can be used to adjust the intensity of 12V lighting.

Compact and robust: Its small size and robust construction make it easy to install and suitable for various applications.

Regulatory Compliance: Meets numerous international standards, ensuring product quality and safety.

Technical characteristics:

Weight (Kg) 0.270

Nominal input voltage 24 VDC

Input range, specifications met 24 ... 32 VDC

Rated output voltage 13.8 VDC

adjustable voltage 12/ 15 VDC

Adjustable voltage 12 ... 15 VDC

maximum output power 70 W

Maximum output current (A) 5

Continuous output current at 40 °C up to 5 A

Efficiency >92%.

Dimensions: 50x98x88 mm

Weight: 0.27 kg
Input voltage: 24-32 VDC
Operating temperature: -10°C to +40°C

If you are looking for a product with similar characteristics [CLICCA QUI](#).

Images and technical data are purely indicative.

Technical Sheet

Product dimensions (mm)

Maximum output current (A)	5
Weight (Kg)	0.270
Nominal input voltage	24 VDC
Input range, specifications met	24 .. 32 VDC
nominal output voltage	13.8 VDC
adjustable tension	12/ 15 vdc
Adjustable tension	12 .. 15 VDC
maximum power output	70 W