



MOSA GE 7000 BBM-L Generator set 6,7 KVA AVR STAGE V

Reference:

MOSA GE 7000 BBM-L Generator set 6,7 KVA AVR STAGE V

MOSA GE 7000 BBM-L: Your energy always at hand

Always key everywhere MOSA GE 7000 BBM-L Generator Set 6.7 KVA is your ideal companion to tackle any situation. With a 420 cm³ Briggs&Stratton XR2100 engine, this single-phase generator can deliver a maximum power output of 6.7 KVA, ensuring reliable and continuous operation.

Perfect for every need

Customizable power: Choose between a maximum power output of 6.7 KVA and a continuous-use output of 6 KVA, tailoring the generator to your specific needs.

Compact and lightweight: At 91 kg, the MOSA GE 7000 BBM-L is easy to transport and place wherever you need it.

Quiet: With its low noise level (99 dB(A) at 1 meter and 74 dB(A) at 7 meters), you can use it without disturbing others.

Durable and Reliable: Designed for durability, the MOSA GE 7000 BBM-L is built with high-quality materials and meets Stage 5 emission regulations.

Easy to use: The pull start and mechanical voltage regulator make operating the generator simple and intuitive.

Technical Specifications MOSA GE7000 BBM-L:

Phase Type Single Phase

Maximum single-phase power (KW) 6

Single-phase continuous use power (KW) 5.4

Maximum single-phase power (KVA) 6.7

Single phase continuous use power (KVA) 6

Fuel Gasoline

Frequency (Hz) 50

Voltage (V) 230

Engine Briggs&Stratton XR2100, 4-stroke, OHV

Engine RPM (rpm) 3000

RPM regulator Mechanical

Recoil ignition

Recoil start

Displacement (cm³) 420

Number of cylinders 1

Oil capacity (L) 1.1

Cooling Air

Alternator SYNCHRONOUS, SINGLE-PHASE, SELF-CONTROLLED

Bore per stroke (mm) 90 x 66

Emissions Standards Stage 5

Weight (kg) 91

Sound power 99 dB(A) (74 dB(A) @ 7m)

Protection class G2

Product dimensions (mm) 770 x 630 x 520

If you are looking for another product like the MOSA GE7000 BBM generator set then you can browse our catalog for more [terrestrial generator sets](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	6
Continuous power single phase (KW)	5.4
Maximum power single phase (KVA)	6.7
Continuous power single phase (KVA)	6
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Engine	Briggs&Stratton XR2100, 4 stroke, OHV
Emissions Regulations	Stage 5

Engine rpm (rpm)	3000
Speed governor	Mechanical
Ignition	Recoil
Starting system	Pull starter
Engine capacity (cm ³)	420
Number cylinders	1
Oil capacity (L)	1.1
Cooling	Air
Alternator	SINCRONO, MONOFASE, AUTOECCITATO, AUTOREGOLATO
Bore x stroke (mm)	90 x 66
Tank capacity (L)	20
Product dimensions (mm)	770 x 630 x 520
Running time (h)	7.5
Acoustic power	99 dB(A) (74 dB(A) @ 7m)
Weight (Kg)	91
classe di protezione	G2