



MOSA MPA50H Motopump for dark water 500L/min

Reference: C5600000

MOSA MPA50H Mud Water Pump 500L/min

The MOSA MPA50H is a high-quality motor pump designed for draining dirty water. Thanks to its robust structure and powerful Honda GX200 engine. The MOSA MPA50H is the ideal choice for those looking for a powerful, reliable, and versatile mud water pump. Thanks to its advanced technical features, it can meet the needs of individuals, professionals, and farms.

Main Features MOSA MPA50H:

Powerful Engine: The Honda GX200 4-stroke petrol engine ensures high performance and reliability.

High Flow Rate: The MOSA MPA50H offers a maximum flow rate of 500 liters per minute, allowing you to quickly complete even the most demanding tasks.

High Head: The pump can lift water up to 90 meters high, making it suitable for various applications.

Effective Suction: The maximum suction lift of 8 meters allows you to draw water even from deep wells or tanks.

Versatile: The MOSA MPA50H can be used for various applications, including:

Draining dirty water from construction sites, ditches, ponds, and swimming pools.

Irrigation of fields and gardens, and much more!

Technical Specifications MOSA MPA50H:

Suction connection diameter: 50 mm (2 inches)
Connection thread: BSP pipe external thread
Delivery volume: 500 L/min
Maximum suction lift: 8 m
Engine: Honda GX200 high speed
Engine type: 4-stroke air-cooled forced air gasoline engine
Displacement: 196 cm³
Continuous rated power: 3.7 kW
Maximum rated power: 4.6 kW
Engine speed: 3,600 rpm
Fuel tank capacity: 3.1 liters
Operating time: Approximately 1.5 hours

Starting: Recoil
Viscosity: Clear water
Net weight: 34.6 kg
Dimensions: 550 x 437 x 457 mm
Fuel: Gasoline
Total head: 90 m
Discharge connection diameter: 50 mm (2 inches) / 25 mm (1 inch) x 2

If you are looking for a product with similar features [CLICK HERE](#).
Images and technical data are purely indicative.

Technical Sheet

| | |
|------------------------------------|-----------------------------------|
| Fuel | Gasoline |
| Engine | HONDA GX200 high rotation |
| Engine rpm (rpm) | 3.600 |
| Starting system | Pull starter |
| Engine capacity (cm ³) | 196 |
| Nominal power continuous | 3.7 kW |
| Product dimensions (mm) | 550 x 437 x 457 |
| Total head (m) | 90 |
| Fuel tank capacity (L) | 3.1 |
| Net weight kg | 34,6 |
| connection diameter | Suction: 50 mm (2 in) |
| Connection thread | BSP external pipe thread |
| delivery volume | 500 L/min |
| Maximum suction head | 8 m |
| Motor type | Air-cooled 4-stroke petrol engine |
| Max Rated Power | 4.6 kW |
| tempo di funzionamento | approx. 1.5 hours |
| Viscosity | Clear water |
| Connection diameter - Drain | 50 mm (2 in) / 25 mm (1 in)×2 |