

PRAMAC GSW170I COFANATO CON QUADRO COMANDO AUTOMATICO

Reference: SU161TCAY02 /



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	131.2
Continuous power three phase (KW)	126.4
Maximum power three phase (KVA)	164
Continuous power three phase (KVA)	158
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	FPT NEF67TM3A, turbo aftercooler
Emissions Regulations	Stage 2
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	6
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	17.2
Cooling	Water
Alternator	Mecc Alte ECP34-2L, brushless
Poles	4
Fuel tank capacity (L)	240
Consumption (L/h)	27.1 at 75% of the load / 35.6 at 100% of the load

Running time (h)	8.9 at 75% of the load / 6.7 at 100% of the load
Acoustic power	96 dB(A)
Acoustic pressure	67 dB(A) at 7 m
Length (mm)	3400
Width (mm)	1250
Height (mm)	1770
Dry weight (Kg)	2057
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	FPT Iveco