

GENERATOR SET 44KVA SILENT STAGEV



Reference: GE44SSVNB

44KVA Silenced Generator Set STAGEV

44KVA Silenced Generator Set STAGEV is a high-quality three-phase generator, designed to provide reliable and quiet power in a wide range of applications. With a maximum power of 44 kVA (40 kW), this generator set is ideal for powering construction sites, outdoor events, emergency situations and other applications that require a stable and quiet power source.

Key Features:

YANMAR Stage V Engine:

The YANMAR 4TNV98C engine ensures high efficiency and low emissions, in compliance with Stage V regulations.

The engine speed of 1500 rpm ensures stable and constant power delivery.

LINZ Alternator:

The LINZ PRO18 ME/4 alternator provides a stable voltage of 230/400V at 50Hz, ensuring compatibility with various equipment.

Superior Quietness:

Thanks to its super silenced configuration, this generator set produces only 62 dB(A) at 7 meters, making it ideal for noise-sensitive environments.

Autonomy and Capacity:

The 120-liter fuel tank offers excellent autonomy, with a consumption of 7.2 lt/h at 75% load.

Robust and Reliable Design:

With a dry weight of 1280 Kg and dimensions of 2260x900x1420 mm, this generator set is built to last.

Water cooling ensures efficient operation even under high load conditions.

Advanced Functionality:

Electronic speed governor for optimal stability.

Electric start for easy and quick start-up.

Technical Specifications:

Phase type: Single phase/Three phase
Maximum three-phase power: 40 kW
Maximum three-phase power: 44 kVA
Frequency: 50 Hz
Voltage: 230 / 400 V
Engine: YANMAR 4TNV98C
Engine speed: 1500 rpm
Speed governor: Electronic
Start: Electric
Displacement: 3319 cm³
Number of cylinders: 4
Cooling: Water
Alternator: LINZ PRO18 ME/4
Number of poles: 4
Fuel tank capacity: 120 liters
Consumption: 7.2 lt/h (specific consumption at 75% load)
Sound pressure: 62 dB(A) at 7 meters
Length: 2260 mm
Width: 900 mm
Height: 1420 mm
Dry weight: 1280 Kg
Silenced: Yes
Super silenced: Yes
Product type: Generator set
Engine brand: LINZ
Emission standard: Stage 5

If you are looking for a product with similar characteristics click [HERE](#).

Images and technical data are not binding. Always consult the technical data sheet issued by the manufacturer.
Manel Service does not assume responsibility for any changes made by the manufacturer.

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	40
Maximum power three phase (KVA)	44
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	YANMAR 4TNV98CT
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	3319

Number cylinders	4
Cooling	Water
Alternator	LINZ PRO18 ME/4
Poles	4
Fuel tank capacity (L)	120
Consumption (L/h)	7.2 lt/h Specific consumption at 75% load
Acoustic pressure	62 dB(A) at 7 m
Length (mm)	2260
Width (mm)	900
Height (mm)	1420
Dry weight (Kg)	1280
Silenced	Yes
Super silenced	Yes
Product type	Generator
Engine manufacturer	LINZ