

PRAMAC GSW200P COFANATO CON QUADRO COMANDO MANUALE

Reference: SU191TPAX00



Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	162.41
Continuous power three phase (KW)	146.18
Maximum power three phase (KVA)	203.01
Continuous power three phase (KVA)	182.73
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	PERKINS 1106A-70TAG3, turbocharged
Speed governor	Mechanical
Starting system	Electric
Engine capacity (cm ³)	7000
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	11.9
Cooling	Water
Alternator	Mecc Alte ECO38-2SN/4, brushless
Poles	4
Fuel tank capacity (L)	340
Consumption (L/h)	30.9 at 75% of the load / 40.1 at 100% of the load
Running time (h)	11 at 75% of the load / 8.5 at 100% of the load

Acoustic power	97 dB(A)
Acoustic pressure	68 dB(A) at 7 m
Length (mm)	3400
Width (mm)	1250
Height (mm)	1770
Dry weight (Kg)	2088
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Perkins