



IDROFOGLIA LZ25W-444LBd/SP Motor pump 200m³/h StageV

Reference: IF444LB

IDROFOGLIA LZ25W-444LBd/SP Motor Pump 200m³/h StageV

IDROFOGLIA LZ25W-444LBd/SP Motor Pump 200m³/h StageV is a high-performance diesel motor pump, designed for applications that require a powerful and constant water flow. With a maximum flow rate of 200 liters per minute, this motor pump is ideal for agricultural irrigation, construction site drainage, and other activities that require efficient pumping.

Key Features:

Powerful and Efficient Engine:

KOHLER KDW 1404 diesel engine

4 cylinders, 1372 cm³ displacement

Liquid cooling

Electric start

Compliant with Stage V emission standards

Pumping Performance:

Maximum flow rate: 200 liters/minute

Delivery and suction diameter: 4 inches

Maximum suction: -8 meters

Robust Construction:

Cast iron pump body

Self-priming pump

Technical Details:

Fuel: Diesel

Engine: KOHLER KDW 1404

Start: Electric

Displacement: 1372 cm³

Number of cylinders: 4

Cooling: Liquid

Maximum suction: -8 m

Delivery diameter: 4"

Delivery diameter: 4"

Maximum flow rate: 200 Lt/min

Main body material: Cast iron

Pump type: SELF-PRIMING PUMP

Engine Brand: Kohler

Emission Standards: Stage 5

If you are looking for a product with different technical characteristics [CLICK HERE](#).

Images and technical data are not binding. Always consult the technical data sheet issued by the manufacturer.
Manel Service does not assume responsibility for any changes made by the manufacturer.

Technical Sheet

Fuel	Diesel
Engine	Kohler KDW 1404
Emissions Regulations	Stage 5
Starting system	Elettrico
Engine capacity (cm ³)	1372
Number cylinders	4
Cooling	Liquid
Pump type	SELF-PRIMING PUMP
Maximum output capacity (Lt/min)	200
Main body material	Ghisa
Outlet diameter thread type (mm/inches)	4"
Length (mm)	2300
Width (mm)	1160

Height (mm)	1550
Engine manufacturer	Kohler
Weight (Kg)	500
Maximum suction	-8 m
