

SCHENKER ZEN 30 TOUCH

Reference: ZEN30TOUCH



SCHENKER ZEN 30 TOUCH NAUTICAL WATERMAKER WITH A CAPACITY OF 30 L / h

The Schenker ZEN 30 TOUCH watermaker is a quiet, small, lightweight, efficient and convenient nautical watermaker. It can be installed in all positions, horizontally and vertically.

The indicated flow rates are nominal and therefore may vary by $\pm 20\%$ depending on actual operating conditions.

The power consumption of the Schenker ZEN 30 marine desalinator is up to 80% lower than conventional systems. For example, only 110 W are needed to produce 30 liters per hour of fresh water. The normal engine recharging is therefore largely sufficient to replenish the energy consumed, without the need for a generator.

Thanks to the very low power consumption, the Schenker ZEN 30 TOUCH watermaker can be powered directly from the batteries. The desalinator can also be installed without a generator set.

The use of the Schenker ZEN 30 TOUCH marine watermaker is extremely simple, as no adjustment is required. In fact, all systems are equipped with automatic pressure regulation. No direct access to the watermaker is required. All functions are carried out remotely via the remote panel.

The Schenker ZEN 30 watermaker does not use high-pressure pumps. The result is extremely quiet operation and a total absence of vibrations.

In the 2.0 systems, all components potentially subject to wear such as o-rings and traditional hydraulic seals have been eliminated. The sealing and sliding elements are made with innovative pads made with nano-technologies. These materials exhibit an abrasion resistance up to 15 times higher than steel.

Schenker plants, as an alternative to the high-pressure pumps of traditional plants, use the new patented ENERGY RECOVERY SYSTEM[®], which amplifies the pressure provided by low-pressure pumps, allowing a very high energy efficiency. The typical power consumption of a Schenker watermaker is only 4 watts/liter.

The ERS is designed specifically for marine applications and is made of materials that are completely impervious to saltwater. Moving parts are minimized, thanks to the patented solution that eliminates the need for pilot valves.

SCHENKER ZEN TECHNICAL SPECIFICATIONS 30

Power: 110 W
Power supply: 12 / 24 VDC
Flow rate: 30 Lt/h
Membranes: n.1 2.5" x 21"
Length: 715.9 mm
Width: 133 mm
Height: 299.5 mm
Weight: 19 Kg

TOUCH PANEL

Remote start/stop
Timer
Automatic rinse
Intensive rinse
Periodic rinse
Hour counter
Automatic start-up
Assisted maintenance
Salinity monitoring (optional)
Flow meter (optional)
Pressure meter (optional)
Tank level switch control
Dimensions: 120 x 80 mm

The Schenker ZEN 30 TOUCH Nautical Desalinator Kit contains:

- Desalinator with Energy Recovery System
- Feed pump with seawater filter
- Activated carbon filter with solenoid valve
- Mains filter sea intake
- Filter key
- Non return valve
- Fresh water production hose (5 meters)
- Remote panel
- Installation kit (assortment of screws and fittings)
- Instruction manual

Standard functions:

- Automatic pressure regulation
- High pressure lockout

Remote control functions:

- Remote start/stop
- Desalter flow
- Timed operation

Discover all our [nautical watermakers by clicking here](#)

Images and technical data are not binding. Please always consult the technical data sheet issued by the manufacturer. Manel Service accepts no liability for any changes made by the manufacturer or any typing errors.

Technical Sheet

Power (W)	110
Length (mm)	715.9
Width (mm)	130
Height (mm)	299.5
Feed Type	12 / 24 VDC
Production for hour at 25°C (Lt/h)	30
Daily production at 25°C (Lt/day)	720

Membranes	n.12.5" x 21"
Remote panel	Digital
Product type	Watermaker
