

## PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

Reference: SG201TWAW00 /



### Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	176
Continuous power three phase (KW)	162.14
Maximum power three phase (KVA)	220
Continuous power three phase (KVA)	202.67
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Engine	VOLVO TAD733GE, turbo intercooled
Emissions Regulations	Stage 2
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	7150
Number cylinders	6
Cylinders' position	In line
Oil capacity (L)	34
Cooling	Water
Alternator	Mecc Alte ECO38-2SN/4, brushless
Poles	4
Fuel tank capacity (L)	400
Consumption (L/h)	34.9 at 75% of the load / 46.5 at 100% of the load

Running time (h)	11.5 at 75% of the load / 8.6 at 100% of the load
Length (mm)	2650
Width (mm)	1180
Height (mm)	1965
Dry weight (Kg)	2026
Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Volvo