

PRAMAC GSW220V COFANATO CON QUADRO COMANDO MANUALE

Reference: SU201TWAX00



Technical Sheet

| | |
|------------------------------------|--|
| Phase | Three phase |
| Maximum power three phase (KW) | 176 |
| Continuous power three phase (KW) | 162.14 |
| Maximum power three phase (KVA) | 220 |
| Continuous power three phase (KVA) | 202.67 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 400 |
| Engine | VOLVO TAD733GE, turbo intercooled |
| Emissions Regulations | Stage 2 |
| Speed governor | Electronic |
| Starting system | Electric |
| Engine capacity (cm ³) | 7150 |
| Number cylinders | 6 |
| Cylinders' position | In line |
| Oil capacity (L) | 34 |
| Cooling | Water |
| Alternator | Mecc Alte ECO38-2SN/4, brushless |
| Poles | 4 |
| Fuel tank capacity (L) | 350 |
| Consumption (L/h) | 34.9 at 75% of the load / 46.5 at 100% of the load |

| | |
|---------------------|---|
| Running time (h) | 10 at 75% of the load / 7.5 at 100% of the load |
| Acoustic power | 94 dB(A) |
| Acoustic pressure | 65 dB(A) at 7 m |
| Length (mm) | 3400 |
| Width (mm) | 1250 |
| Height (mm) | 1980 |
| Dry weight (Kg) | 2540 |
| Silenced | Yes |
| Super silenced | Yes |
| ATS Switch device | No ATS |
| Voltage regulator | AVR |
| Engine manufacturer | Volvo |