

Generator Set 710kVA Silenced 370L



Reference: NB - GE710kVA

Soundproof Generator 710kVA 370L

The Soundproof Generator 710kVA 370L is designed to provide constant and safe electrical power in any situation. Thanks to the powerful Hyundai engine and the Leroy Somer alternator, this generator guarantees high performance and operational continuity, becoming an indispensable support for companies, construction sites, and facilities requiring high power.

The super soundproof canopy minimizes acoustic impact, making the Soundproof Generator 710kVA 370L suitable not only for industrial environments but also for urban contexts or events where silence is essential. Robust, efficient, and easy to manage, it combines power and reliability in a single professional solution.

Main features – Soundproof Generator 710kVA 370L:

Three-phase maximum power: 710 KVA
Continuous three-phase power: 568 KW
Fuel: Diesel
Voltage: 230/400 V
Engine: HYUNDAI DP180LB
Fuel tank capacity: 370 L
Alternator: Leroy Somer TAL0473 F
Starting: Automatic
Length: 5000 mm
Width: 1900 mm
Height: 2350 mm
Weight: 5690 Kg

Power, efficiency and silence in a single Soundproof Generator 710kVA 370L:

The **Soundproof Generator 710kVA 370L** has been designed to ensure maximum operational continuity in every situation. The combination of the powerful Hyundai engine and the Leroy Somer alternator delivers consistent and long-lasting performance, while the super soundproof canopy drastically reduces noise, making it suitable even in environments where noise is a critical factor.

The construction quality of the Soundproof Generator 710kVA 370L is built to last: powder-coated carbon steel, class 1 sound-absorbing materials, and anti-vibration systems guarantee strength and stability even under the toughest conditions. Every detail, from reinforced access doors to integrated safety systems, has been designed to make use and maintenance easier.

Looking for a generator with different technical features? [CLICK HERE](#) to explore the section dedicated to generators from leading specialized brands.

Technical Sheet

| Phase | Three phase |
|------------------------------------|------------------------------|
| Maximum power three phase (KW) | 568 |
| Continuous power three phase (KW) | 568 |
| Maximum power three phase (KVA) | 710 |
| Continuous power three phase (KVA) | 640 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 / 400 |
| Engine | HYUNDAI DP180LB |
| Emissions Regulations | NON EMISSIONATO |
| Engine rpm (rpm) | 1500 |
| Speed governor | Electronic |
| Starting system | Automatico |
| Engine capacity (cm ³) | 18273 |
| Number cylinders | 10 |
| Cylinders' position | In line |
| Cooling | Water |
| Alternator | Leroy Somer TAL0473 F |
| Poles | 4 |
| Protection degree | IP23 |
| Fuel tank capacity (L) | 370 |
| Consumption (L/h) | 103.8 Lt/h al 75% del carico |
| Running time (h) | 3.34 h al 75% del carico |
| Acoustic pressure | 75 dB(A) at 7 m |
| Length (mm) | 5000 |
| Width (mm) | 1900 |
| Height (mm) | 2350 |
| Dry weight (Kg) | 5690 |
| Silenced | Yes |
| Super silenced | No |
| ATS Switch device | Optional ATS |
| Lead-acid battery | 2X12V 200Ah |

Insulation Class

H