



PRAMAC GSW22P ENCLOSURE WITH MANUAL CONTROL PANEL

Reference: SU200TPAR00

PRAMAC GSW22P MCP Three-Phase 17.2 KW Super Silent AVR Generator Set

The PRAMAC GSW22P three-phase generator set with 17.2 KW power output features a diesel-powered engine running at 1500 RPM. The PRAMAC GSW22P generator set is equipped with electric start. The three-phase alternator of the PRAMAC GSW22P generator set is a brushless Mecc Alte with an AVR voltage regulator. The Perkins diesel engine makes the GSW22P generator set very reliable as it is built and designed using high-quality materials and has a base that can be easily forked for transport with trolleys.

Thanks to its casing, this generator set is super silent. Moreover, it is easy to transport, install, and position due to its compact size. This model is ideal for emergency network use, construction sites, mobile workshops, and industrial applications. The PRAMAC GSW22P three-phase generator set is suitable for outdoor use on construction sites or for small professional outdoor jobs.

Technical specifications of the PRAMAC GSW22P MCP Three-Phase Generator Set:

- Maximum three-phase power: 17.2 KW
- Continuous use three-phase power: 16.08 KW
- Fuel: Diesel
- Voltage: 400 V
- Frequency: 50 Hz
- Engine: Perkins 404D-22G
- Starting system: Electric
- Consumption: 5.3 Lt/h at 100% load
- Length: 1800 mm
- Width: 850 mm
- Height: 1260 mm
- Weight: 730 Kg
- AVR

Sockets:

- 1 x 3P+N+T CEE 400V 32A
- 1 x 3P+N+T CEE 400V 16A
- 2 x 2P+T CEE 230V 16A
- 1 x 230V 16A SCHUKO

The PRAMAC GSW22P power generator is a professional diesel generator set developed by Pramac that offers many solutions for a variety of applications, from continuous use to emergency network use. The PRAMAC GSW22P power generator complies with safety and noise emission standards and can be used in both residential and industrial settings. The GSW22P generator set is equipped with a reliable Perkins diesel engine and various control panel solutions, accessories, and add-ons, making it versatile and capable of meeting the most demanding customer needs.

If you are looking for a generator set like the GSW22P MCP three-phase power generator, we recommend browsing our catalog of [terrestrial generator](#) sets to find the one that best meets your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	17.2
Continuous power three phase (KW)	16.08
Maximum power three phase (KVA)	21.5
Continuous power three phase (KVA)	20.1
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	400
Sockets configuration	1 x 400V 32A 3P+N+T - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO
Engine	PERKINS 404D-22G, naturally aspirated
Emissions Regulations	STAGE 3A
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	2216
Number cylinders	4
Cylinders' position	In line
Oil capacity (L)	10.6
Cooling	Water
Alternator	Mecc Alte ECP28-M/4, brushless
Poles	4
Fuel tank capacity (L)	68
Consumption (L/h)	4 at 75% of the load / 5.3 at 100% of the load
Running time (h)	17.1 at 75% of the load / 12.9 at 100% of the load
Acoustic power	87 dB(A)
Acoustic pressure	58 dB(A) at 7 m

Length (mm)	1800
Width (mm)	850
Dry weight (Kg)	98
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Perkins