



Generator set Super-Silenced Manual Control 33KVA Stage3A

Reference: GQSS33A

33KVA Stage3A Super-Silent Manual Control Generator

The Yanmar 4TNV98 33 kVA (26.4 kW) three-phase diesel generator with manual control is the perfect solution for those who need a powerful and reliable power supply in any situation. This super-silent generator, compliant with Stage 3A emissions regulations, combines high performance with extremely quiet operation, ideal for construction sites, events and noise-sensitive environments.

Equipped with a 4-stroke, 4-cylinder, 3319 cm³ diesel engine, operating at 1500 rpm, it guarantees a maximum power of 33 kVA and continuous use of 30 kVA, ensuring continuous and stable power supply. The starter is electric, while the mechanical speed governor allows for simple and precise control of the engine speed.

The generator is equipped with a 4-pole LINZ PRO18S C/4 alternator with AVR voltage regulator, which maintains a constant voltage of 230/400 V and 50 Hz frequency, thus protecting the connected equipment. The integrated manual panel facilitates the management of the generator, making it simple to use even without automatic control systems.

With a 70-liter tank capacity and a consumption of 5.2 liters per hour, the generator offers a runtime of approximately 13 hours, perfect for extended work without the need for frequent refueling. Its compact dimensions (1750x700x1100 mm) and dry weight of 570 kg make it easy to transport and install.

The socket configuration includes a CEE 63A 400V 5-pole and an additional CEE socket, ensuring versatility and safety in electrical connections.

Choose the super-silenced three-phase diesel generator with 33 kVA manual control panel to have power, silence and environmental compliance in a single high-quality product.

Technical characteristics:

Maximum power: 26.4 kW (33 kVA)

Continuous use power: 24 kW (30 kVA)

Fuel: Diesel

Engine: Yanmar 4TNV98, 4-stroke, 4-cylinder, 3319 cm³

Engine speed: 1500 rpm, electric start, mechanical speed governor

Cooling: Water

Alternator: LINZ PRO18S C/4, 4-pole, AVR voltage regulator

Frequency: 50 Hz

Voltage: 230/400 V

Fuel tank capacity: 70 L with consumption 5.2 L/h and autonomy approximately 13 h

Dimensions: 1750 mm (length) x 700 mm (width) x 1100 mm (height)

Dry weight: 570 kg

Noise level: silenced, super silenced

Emissions standard: Stage 3A

Socket configuration: 1 x CEE 63A 400V 5P, 1 x CEE

If you are looking for a product with different features [Click HERE](#). You'll find a product category to suit your needs.

The image is purely indicative.

Technical Sheet

Phase	Three phase
Maximum power three phase (KW)	26.4
Continuous power three phase (KW)	24
Maximum power three phase (KVA)	33
Continuous power three phase (KVA)	30
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x CEE 63A 400V 5P 1 x CEE 32A 400V 5P 1 x CEE 16A 230V 3P
Engine	Yanmar 4TNV98, 4 stroke
Emissions Regulations	STAGE 3A
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	3319
Number cylinders	4
Cooling	Water
Alternator	LINZ PRO18S C/4
Poles	4
Fuel tank capacity (L)	70
Consumption (L/h)	5.2

Running time (h)	13 h (Approx.)
Length (mm)	1750
Width (mm)	700
Height (mm)	1100
Silenced	Yes
Super silenced	Yes
Voltage regulator	AVR
